

**AUTOMATIC WATER COOLING**  
**AWC1 CABINET & WALL MOUNTED**  
**AWC2 CONSOLE MOUNTED**  
 FOR ALL DIRECT STEAM FLOOR MODEL KETTLES & MIXER KETTLES

Project \_\_\_\_\_  
 Item \_\_\_\_\_  
 Quantity \_\_\_\_\_  
 FCSI Section 11400 \_\_\_\_\_  
 Approved \_\_\_\_\_  
 Date \_\_\_\_\_

**Models**

WALL OR STAND MOUNTED MODELS:

- MODEL AWC1



**Standard Features**

- Automatically injects cold water into the steam jacket, slowing down the cooking process.
- All exterior surfaces are type 304 Stainless Steel
- 115 Volt, 60 Cycle, 1 Phase standard. 220 Volt, 60 cycle, 1 Phase optional. Cord and Plug supplied by others.
- All connections are a 3/4" NPT.
- Standard with six 9/32" holes for wall mounting.
- Internal Components contain:
  - (1) 3/4" Steam Solenoid Valve,
  - (3) 3/4" Water Solenoid Valves,
  - (1) 3/4" Check Valve,
  - (1) 220/115V Transformer (220 volt optional)
  - (1) On/Off Switch.

**Short Form Specifications**

Shall be CLEVELAND, Model AWC \_\_\_\_\_ Automatic Water Cooling; 115 Volt, 60 Cycle, 1 Phase; All exterior surfaces are type 304 Stainless Steel. Internal Components contain: (1) 3/4" Steam Solenoid Valve, (3) 3/4" Water Solenoid Valves, (1) 3/4" Check Valve, (1) 220/115V Transformer (220 volt optional) and (1) On/Off Switch.

**Options & Accessories**

\* For Console Mounted Models AWC2:

- Requires Console Mounting Option (CM)
- Available only on KDL floor model kettles and MKDL mixer kettles.

