



PART NUMBER	REV.	REAM ORIFICE SIZE 'A'	GAS TYPE	KETTLE SIZE	ELEVATION ABOVE SEA LEVEL	FIRING RATE BTU/HR.
KE53403-8	G	0.219	NATURAL	40 GAL.	SEA LEVEL UPTO 2000'	140,000
KE53403-5	G	0.177	PROPANE			190,000
KE53403-6	G	0.265	NATURAL	60,80, 100 GAL.	2000' UPTO 4000'	133,000
KE53403-7	G	0.209	PROPANE	180,000		
KE53403-8	G	0.219	NATURAL	40 GAL.	4000' UPTO 6000'	126,350
KE53403-9	G	0.173	PROPANE	171,500		
KE53403-10	G	0.250	NATURAL	60,80, 100 GAL.	6000' UPTO 8000'	120,000
KE53403-11	G	0.201	PROPANE	163,000		
KE53403-12	G	0.213	NATURAL	40 GAL.	8000' UP TO 10,000'	114,000
KE53403-13	G	0.169	PROPANE	155,000		
KE53403-10	G	0.250	NATURAL	60,80, 100 GAL.	SEE ENGINEERING	
KE53403-14	G	0.196	PROPANE	OTHER		
KE53403-15	G	0.205	NATURAL	40-100	UP TO 2000'	
KE53403-16	G	0.166	PROPANE	40-100	UP TO 2000'	140,000
KE53403-17	G	0.234	NATURAL	40 GAL.	UP TO 2000'	140,000
KE53403-18	G	0.191	PROPANE	60-100	UP TO 2000'	170,000
KE53403-11	G	0.201	NATURAL	40	UP TO 2000'	140,000
KE53403-20	G	0.161	PROPANE	60-100	UP TO 2000'	190,000
KE53403-17	G	0.234	NATURAL	40-100	UP TO 2000'	
KE53403-22	G	0.187	PROPANE	40-100	UP TO 2000'	
KE53403-23	B	SEE ENGINEERING	OTHER	40-100	UP TO 2000'	
KE53403-24	B	0.437	HONG KONG TOWN GAS	40-100	UP TO 2000'	140,000
KE53403-25	B	0.312	MANUF.	40 GAL.	UP TO 2000'	140,000
KE53403-26	B	0.344	MANUF.	60-100	UP TO 2000'	170,000
KE53403-13	B	0.169	BUTANE	40	UP TO 2000'	140,000
KE53403-27	B	0.203	BUTANE	60-100	UP TO 2000'	190,000

NOTES:
 ALL UNITS ARE MANUFACTURED & APPROVED AT SEA LEVEL UP TO 2000FT ONLY,
 ELEVATION ORIFICES ARE PROVIDED WHEN REQUESTED TO BE INSTALLED & CONFIRMED
 AT CUSTOMER'S SITE BY QUALIFIED TECHNICIANS.