

## Rating and Approval Document

## 3 Gallon Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
KET-3-T	S	200	1	2	See Note#1	3781	18.9	10	5/16	5000	230	1	18.9			X	X		
	S	208	1	2	See Note#1	4089	19.7	10	5/16	5000	230	1	19.7	X	X	X	X		
	S	220	1	2	See Note#1	4575	20.8	10	5/16	5000	230	1	20.8			X	X		
	S	230	1	2	See Note#1	5000	21.7	10	5/16	5000	230	1	21.7			X	X		
	S	240	1	2	See Note#1	5444	22.7	10	5/16	5000	230	1	22.7	X	X	X	X		
NOT AVAILABLE	<del>S</del>	<del>380</del>	<del>1</del>	<del>2</del>	<del>See Note#1</del>	<del>4192</del>	<del>11.0</del>	<del>14</del>	<del>7/16</del>	<del>5000</del>	<del>415</del>	<del>1</del>	<del>11.0</del>	<del></del>	<del></del>	<del>X</del>	<del>X</del>	<del></del>	<del></del>
NOT AVAILABLE	<del>S</del>	<del>400</del>	<del>1</del>	<del>2</del>	<del>See Note#1</del>	<del>4645</del>	<del>11.6</del>	<del>14</del>	<del>7/16</del>	<del>5000</del>	<del>415</del>	<del>1</del>	<del>11.6</del>	<del></del>	<del></del>	<del>X</del>	<del>X</del>	<del></del>	<del></del>
NOT AVAILABLE	<del>S</del>	<del>415</del>	<del>1</del>	<del>2</del>	<del>See Note#1</del>	<del>5000</del>	<del>12.0</del>	<del>14</del>	<del>7/16</del>	<del>5000</del>	<del>415</del>	<del>1</del>	<del>12.0</del>	<del></del>	<del></del>	<del>X</del>	<del>X</del>	<del></del>	<del></del>
NOT AVAILABLE	<del>S</del>	<del>440</del>	<del>1</del>	<del>2</del>	<del>See Note#1</del>	<del>4575</del>	<del>10.4</del>	<del>14</del>	<del>7/16</del>	<del>5000</del>	<del>460</del>	<del>1</del>	<del>10.4</del>	<del></del>	<del></del>	<del>X</del>	<del>X</del>	<del></del>	<del></del>
NOT AVAILABLE	<del>S</del>	<del>480</del>	<del>1</del>	<del>2</del>	<del>See Note#1</del>	<del>5444</del>	<del>11.3</del>	<del>14</del>	<del>7/16</del>	<del>5000</del>	<del>460</del>	<del>1</del>	<del>11.3</del>	<del></del>	<del></del>	<del>X</del>	<del></del>	<del></del>	<del></del>

**NOTES:**

- 1) Most units can be 50 or 60 Hz. Unless otherwise noted the unit will be 60 Hz.
- 2) UL and CSA approvals are for 60 Hz only.
- 3) Units which are CSA certified may include optional power supply cord for units rated up to 24A max.
- 4) Rating Label to be used KE95250

# Rating and Approval Document

# 6 Gallon Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp/ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
KET-6-T	S	200	1	2	See Note#1	5671	28.4	8	5/16	2500	230	3	9.5			X	X		
	S	200	3	3	See Note#1	5671	16.4	12	5/16	2500	230	3	9.5			X	X		
	S	208	1	2	See Note#1	6134	29.5	8	5/16	2500	230	3	9.8	X	X	X	X		
	S	208	3	3	See Note#1	6134	17.0	10	5/16	2500	230	3	9.8	X	X	X	X		
	S	240	1	2	See Note#1	8166	34.0	8	5/16	2500	230	3	11.3	X	X	X	X		
	S	240	3	3	See Note#1	8166	19.6	10	5/16	2500	230	3	11.3	X	X	X	X		
	S	220	1	2	See Note#1	6862	31.2	8	5/16	2500	230	3	10.4			X	X		
	S	220	3	3	See Note#1	6862	18.0	10	5/16	2500	230	3	10.4			X	X		
	S	230	1	2	See Note#1	7500	32.6	8	5/16	2500	230	3	10.9			X	X		
	S	230	3	3	See Note#1	7500	18.8	10	5/16	2500	230	3	10.9			X	X		
	H	200	1	2	See Note#1	9074	45.4	6	5/16	4000	230	3	15.1			X	X		
	H	200	3	3	See Note#1	9074	26.2	8	5/16	4000	230	3	15.1			X	X		
	H	220	1	2	See Note#1	10979	49.9	6	5/16	4000	230	3	16.6			X	X		
	H	220	3	3	See Note#1	10979	28.8	8	5/16	4000	230	3	16.6			X	X		
	H	230	1	2	See Note#1	12000	52.2	6	5/16	4000	230	3	17.4			X	X		
	H	230	3	3	See Note#1	12000	30.1	8	5/16	4000	230	3	17.4			X	X		

# Rating and Approval Document

# 6 Gallon Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp/ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
KET-6-T	H	208	1	2	See Note#1	9814	47.2	6	5/16	4000	230	3	15.7	X	X	X	X		
	H	208	3	3	See Note#1	9814	27.2	8	5/16	4000	230	3	15.7	X	X	X	X		
	H	240	1	2	See Note#1	13066	54.4	6	5/16	4000	230	3	18.1	X	X	X	X		X
	H	240	3	3	See Note#1	13066	31.4	8	5/16	4000	230	3	18.1	X	X	X	X		X
	S	380	1	2	See Note#1	6288	16.5	10	7/16	2500	415	3	5.5			X	X		
	S	380	3	3	See Note#1	6288	9.6	14	7/16	2500	415	3	5.5			X	X		
	S	400	1	2	See Note#1	6968	17.4	10	7/16	2500	415	3	5.8			X	X		
	S	400	3	3	See Note#1	6968	10.1	14	7/16	2500	415	3	5.8			X	X		
	S	416	1	2	See Note#1	7536	18.1	10	7/16	2500	415	3	6.0			X	X		X
	S	416	3	3	See Note#1	7536	10.5	14	7/16	2500	415	3	6.0			X	X		X
	S	440	1	2	See Note#1	6862	15.6	12	7/16	2500	460	3	5.2			X	X		
	S	440	3	3	See Note#1	6862	9.0	14	7/16	2500	460	3	5.2			X	X		
	S	480	1	2	See Note#1	8166	17.0	10	7/16	2500	460	3	5.7			X			
	S	480	3	3	See Note#1	8166	9.8	14	7/16	2500	460	3	5.7			X			
	S	575	4	2	See Note#4	7500	13.0	12	7/16	2500	575	3	4.3			X			
	S	575	3	3	See Note#4	7500	7.5	14	7/16	2500	575	3	4.3			X			
	S	600	4	2	See Note#4	8166	13.6	12	7/16	2500	575	3	4.5			X			
	S	600	3	3	See Note#4	8166	7.9	14	7/16	2500	575	3	4.5			X			

# Rating and Approval Document

# 6 Gallon Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp/ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
KET-6-T	H	380	1	2	See Note#1	10061	26.5	8	7/16	4000	415	3	8.8			X	X		
	H	380	3	3	See Note#1	10061	15.3	12	7/16	4000	415	3	8.8			X	X		
	H	400	1	2	See Note#1	11148	27.9	8	7/16	4000	415	3	9.3			X	X		
	H	400	3	3	See Note#1	11148	16.1	12	7/16	4000	415	3	9.3			X	X		
	H	416	1	2	See Note#1	12058	29.0	8	7/16	4000	415	3	9.7			X	X		X
	H	416	3	3	See Note#1	12058	16.7	10	7/16	4000	415	3	9.7			X	X		X
	H	440	1	2	See Note#1	10979	25.0	8	7/16	4000	460	3	8.3			X	X		
	H	440	3	3	See Note#1	10979	14.4	12	7/16	4000	460	3	8.3			X	X		
	H	480	1	2	See Note#1	13066	27.2	8	7/16	4000	460	3	9.1	X		X			
	H	480	3	3	See Note#1	13066	15.7	12	7/16	4000	460	3	9.1	X		X			
	H	575	1	2	See Note#1	12000	20.9	10	7/16	4000	575	3	7.0			X			
	H	575	3	3	See Note#1	12000	12.0	14	7/16	4000	575	3	7.0			X			
	H	600	1	2	See Note#1	13066	21.8	10	7/16	4000	575	3	7.3			X			
	H	600	3	3	See Note#1	13066	12.6	12	7/16	4000	575	3	7.3			X			

**NOTES:**

- 1) Most units can be 50 or 60 Hz. Unless otherwise noted the unit will be 60 Hz.
- 2) UL and CSA approvals are for 60 Hz only.
- 3) Units which are CSA certified may include optional power supply cord for units rated up to 24A max.
- 4) Australian approval No. 1089N-6994-P77 to be added to the Rating Plate
- 5) Rating Label used is KE95250
- 6) Template column is for production control use only

# Rating and Approval Document

# 12 Gallon Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
KET-12-T	S	200	1	2	See Note#1	9074	45.4	6	5/16	4000	230	3	15.1			X	X		
	S	200	3	3	See Note#1	9074	26.2	8	5/16	4000	230	3	15.1			X	X		
	S	208	1	2	See Note#1	9814	47.2	6	5/16	4000	230	3	15.7	X	X	X	X		
	S	208	3	3	See Note#1	9814	27.2	8	5/16	4000	230	3	15.7	X	X	X	X		
	S	240	1	2	See Note#1	13066	54.4	6	5/16	4000	230	3	18.1	X	X	X	X		X
	S	240	3	3	See Note#1	13066	31.4	8	5/16	4000	230	3	18.1	X	X	X	X		X
	S	220	1	2	See Note#1	10979	49.9	6	5/16	4000	230	3	16.6			X	X		
	S	220	3	3	See Note#1	10979	28.8	8	5/16	4000	230	3	16.6			X	X		
	S	230	1	2	See Note#1	12000	52.2	6	5/16	4000	230	3	17.4			X	X		
	S	230	3	3	See Note#1	12000	30.1	8	5/16	4000	230	3	17.4			X	X		
	S	380	1	2	See Note#1	10061	26.5	8	7/16	4000	415	3	8.8			X	X		
	S	380	3	3	See Note#1	10061	15.3	12	7/16	4000	415	3	8.8			X	X		
	S	400	1	2	See Note#1	11148	27.9	8	7/16	4000	415	3	9.3			X	X		
	S	400	3	3	See Note#1	11148	16.1	12	7/16	4000	415	3	9.3			X	X		
	S	416	1	2	See Note#1	12058	29.0	8	7/16	4000	415	3	9.7	X	X	X	X		X
	S	416	3	3	See Note#1	12058	16.7	10	7/16	4000	415	3	9.7	X	X	X	X		X
	S	480	1	2	See Note#1	13066	27.2	8	7/16	4000	460	3	9.1	X		X			
	S	480	3	3	See Note#1	13066	15.7	12	7/16	4000	460	3	9.1	X		X			

# Rating and Approval Document

# 12 Gallon Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.	
KET-12-T	<del>S</del>	<del>575</del>	<del>4</del>	<del>2</del>	<del>See Note#1</del>	<del>12000</del>	<del>20.9</del>	<del>10</del>	<del>7/16</del>	<del>4000</del>	<del>575</del>	<del>3</del>	<del>7.0</del>			X				
	<del>S</del>	<del>575</del>	<del>3</del>	<del>3</del>	<del>See Note#1</del>	<del>12000</del>	<del>12.0</del>	<del>14</del>	<del>7/16</del>	<del>4000</del>	<del>575</del>	<del>3</del>	<del>7.0</del>			X				
	S	440	1	2	See Note#1	10979	25.0	8	7/16	4000	460	3	8.3			X	X			
	S	440	3	3	See Note#1	10979	14.4	12	7/16	4000	460	3	8.3			X	X			
	<del>S</del>	<del>600</del>	<del>4</del>	<del>2</del>	<del>See Note#1</del>	<del>13066</del>	<del>21.8</del>	<del>10</del>	<del>7/16</del>	<del>4000</del>	<del>575</del>	<del>3</del>	<del>7.3</del>			X				
	<del>S</del>	<del>600</del>	<del>3</del>	<del>3</del>	<del>See Note#1</del>	<del>13066</del>	<del>12.6</del>	<del>12</del>	<del>7/16</del>	<del>4000</del>	<del>575</del>	<del>3</del>	<del>7.3</del>			X				
	H	200	1	2	See Note#1	11342	56.7	4	5/16	5000	230	3	18.9			X	X			
	H	200	3	3	See Note#1	11342	32.7	8	5/16	5000	230	3	18.9			X	X			
	H	208	1	2	See Note#1	12268	59.0	4	5/16	5000	230	3	19.7	X	X	X	X			
	H	208	3	3	See Note#1	12268	34.1	8	5/16	5000	230	3	19.7	X	X	X	X			
	H	240	1	2	See Note#1	16333	68.1	4	5/16	5000	230	3	22.7	X	X	X	X			
	H	240	3	3	See Note#1	16333	39.3	6	5/16	5000	230	3	22.7	X	X	X	X			
	H	220	1	2	See Note#1	13724	62.4	4	5/16	5000	230	3	20.8	X		X	X			
	H	220	3	3	See Note#1	13724	36.0	8	5/16	5000	230	3	20.8	X		X	X			
	H	230	1	2	See Note#1	15000	65.2	4	5/16	5000	230	3	21.7			X	X			
	H	230	3	3	See Note#1	15000	37.7	6	5/16	5000	230	3	21.7			X	X			

# Rating and Approval Document

# 12 Gallon Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
KET-12-T	H	380	1	2	See Note#1	12577	33.1	8	7/16	5000	415	3	11.0	X		X	X		
	H	380	3	3	See Note#1	12577	19.1	10	7/16	5000	415	3	11.0	X		X	X		
	H	400	1	2	See Note#1	13935	34.8	8	7/16	5000	415	3	11.6			X	X		
	H	400	3	3	See Note#1	13935	20.1	10	7/16	5000	415	3	11.6			X	X		
	H	416	1	2	See Note#1	15072	36.2	8	7/16	5000	415	3	12.1	X	X	X	X		
	H	416	3	3	See Note#1	15072	20.9	10	7/16	5000	415	3	12.1	X	X	X	X		
	H	440	1	2	See Note#1	13724	31.2	8	7/16	5000	460	3	10.4			X	X		
	H	440	3	3	See Note#1	13724	18.0	10	7/16	5000	460	3	10.4			X	X		
	H	480	1	2	See Note#1	16333	34.0	8	7/16	5000	460	3	11.3	X		X			
	H	480	3	3	See Note#1	16333	19.6	10	7/16	5000	460	3	11.3	X		X			
	H	575	4	2	See Note#1	15000	26.4	8	7/16	5000	575	3	8.7			X			
	H	575	3	3	See Note#1	15000	15.4	12	7/16	5000	575	3	8.7			X			
	H	600	4	2	See Note#1	16333	27.2	8	7/16	5000	575	3	9.4			X			
	H	600	3	3	See Note#1	16333	15.7	12	7/16	5000	575	3	9.4			X			

**NOTES:**

- 1) Most units can be 50 or 60 Hz. Unless otherwise noted the unit will be 60 Hz.
- 2) UL and CSA approvals are for 60 Hz only.
- 3) Australian approval No. 1089N-8023-P78 to be added to the rating plate
- 4) Rating Label to be used KE95250
- 5) Template column is for production control use only

## Rating and Approval Document

## 20 Gallon Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
KET-20-T	S	200	1	2	See Note#1	11342	56.7	4	5/16	5000	230	3	18.9			X	X		
	S	200	3	3	See Note#1	11342	32.7	8	5/16	5000	230	3	18.9			X	X		
	S	208	1	2	See Note#1	12268	59.0	4	5/16	5000	230	3	19.7	X	X	X	X		
	S	208	3	3	See Note#1	12268	34.1	8	5/16	5000	230	3	19.7	X	X	X	X		
	S	240	1	2	See Note#1	16333	68.1	4	5/16	5000	230	3	22.7	X	X	X	X		
	S	240	3	3	See Note#1	16333	39.3	6	5/16	5000	230	3	22.7	X	X	X	X		
	S	220	1	2	See Note#1	13724	62.4	4	5/16	5000	230	3	20.8	X		X	X		
	S	220	3	3	See Note#1	13724	36.0	8	5/16	5000	230	3	20.8	X		X	X		
	S	230	1	2	See Note#1	15000	65.2	4	5/16	5000	230	3	21.7			X	X		
	S	230	3	3	See Note#1	15000	37.7	6	5/16	5000	230	3	21.7			X	X		
	S	380	1	2	See Note#1	12577	33.1	8	7/16	5000	415	3	11.0	X		X	X		
	S	380	3	3	See Note#1	12577	19.1	10	7/16	5000	415	3	11.0	X		X	X		
	S	400	1	2	See Note#1	13935	34.8	8	7/16	5000	415	3	11.6			X	X		
	S	400	3	3	See Note#1	13935	20.1	10	7/16	5000	415	3	11.6			X	X		
	S	416	1	2	See Note#1	15072	36.2	8	7/16	5000	415	3	12.1			X	X		
	S	416	3	3	See Note#1	15072	20.9	10	7/16	5000	415	3	12.1			X	X		
	S	440	1	2	See Note#1	13724	31.2	8	7/16	5000	460	3	10.4			X	X		
	S	440	3	3	See Note#1	13724	18.0	10	7/16	5000	460	3	10.4			X	X		

## Rating and Approval Document

## 20 Gallon Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
KET-20-T	S	480	1	2	See Note#1	16333	34.0	8	7/16	5000	460	3	11.3	X		X			
	S	480	3	3	See Note#1	16333	19.6	10	7/16	5000	460	3	11.3	X		X			
	S	575	4	2	See Note#1	15000	26.4	8	7/16	5000	575	3	8.7			X			
	S	575	3	3	See Note#1	15000	15.4	12	7/16	5000	575	3	8.7			X			
	S	600	4	2	See Note#1	16333	27.2	8	7/16	5000	575	3	9.4			X			
	S	600	3	3	See Note#1	16333	15.7	12	7/16	5000	575	3	9.4			X			
	H	200	1	2	See Note#1	13611	68.1	4	5/16	6000	230	3	22.7				X	X	
	H	200	3	3	See Note#1	13611	39.3	6	5/16	6000	230	3	22.7				X	X	
	H	208	1	2	See Note#1	14721	70.8	3	5/16	6000	230	3	23.6	X	X	X	X		
	H	208	3	3	See Note#1	14721	40.9	6	5/16	6000	230	3	23.6	X	X	X	X		
	H	240	1	2	See Note#1	19599	81.7	3	5/16	6000	230	3	27.2	X	X	X	X		
	H	240	3	3	See Note#1	19599	47.1	6	5/16	6000	230	3	27.2	X	X	X	X		
	H	220	1	2	See Note#1	16469	74.9	3	5/16	6000	230	3	25.0				X	X	
	H	220	3	3	See Note#1	16469	43.2	6	5/16	6000	230	3	25.0				X	X	
	H	230	1	2	See Note#1	18000	78.3	3	5/16	6000	230	3	26.1				X	X	
	H	230	3	3	See Note#1	18000	45.2	6	5/16	6000	230	3	26.1				X	X	

## Rating and Approval Document

## 20 Gallon Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
KET-20-T	H	380	1	2	See Note#1	15092	39.7	6	7/16	6000	415	3	13.2	X		X	X		
	H	380	3	3	See Note#1	15092	22.9	10	7/16	6000	415	3	13.2	X		X	X		
	H	400	1	2	See Note#1	16722	41.8	6	7/16	6000	415	3	13.9			X	X		
	H	400	3	3	See Note#1	16722	24.1	10	7/16	6000	415	3	13.9			X	X		
	H	416	1	2	See Note#1	18087	43.5	6	7/16	6000	415	3	14.5	X		X	X		
	H	416	3	3	See Note#1	18087	25.1	8	7/16	6000	415	3	14.5	X		X	X		
	H	440	1	2	See Note#1	16469	37.4	6	7/16	6000	460	3	12.5			X	X		
	H	440	3	3	See Note#1	16469	21.6	10	7/16	6000	460	3	12.5			X	X		
	H	480	1	2	See Note#1	19599	40.8	6	7/16	6000	460	3	13.6	X		X			
	H	480	3	3	See Note#1	19599	23.6	10	7/16	6000	460	3	13.6	X		X			
	H	575	1	2	See Note#1	18000	31.3	8	7/16	6000	575	3	10.4			X			
	H	575	3	3	See Note#1	18000	18.1	10	7/16	6000	575	3	10.4			X			
	H	600	1	2	See Note#1	19599	32.7	8	7/16	6000	575	3	10.9			X			
	H	600	3	3	See Note#1	19599	18.9	10	7/16	6000	575	3	10.9			X			

NOTES:

- 1) Most units can be 50 or 60 Hz. Unless otherwise noted the unit will be 60 Hz.
- 2) UL and CSA approvals are for 60 Hz only.
- 3) Rating Label to be used KE95250

# Rating and Approval Document

# 25 Gallon Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
KEL-25-T	S	200	1	2	See Note#1	9074	45.4	6	5/16	4000	230	3	15.1			X	X		
KEL-25	S	200	3	3	See Note#1	9074	26.2	8	5/16	4000	230	3	15.1			X	X		
KEP-25	S	208	1	2	See Note#1	9814	47.2	6	5/16	4000	230	3	15.7	X	X	X	X		
	S	208	3	3	See Note#1	9814	27.2	8	5/16	4000	230	3	15.7	X	X	X	X		
	S	240	1	2	See Note#1	13066	54.4	6	5/16	4000	230	3	18.1	X	X	X	X		
	S	240	3	3	See Note#1	13066	31.4	8	5/16	4000	230	3	18.1	X	X	X	X		
	S	220	1	2	See Note#1	10979	49.9	6	5/16	4000	230	3	16.6			X	X		
	S	220	3	3	See Note#1	10979	28.8	8	5/16	4000	230	3	16.6			X	X		
	S	230	1	2	See Note#1	12000	52.2	6	5/16	4000	230	3	17.4			X	X		
	S	230	3	3	See Note#1	12000	30.1	8	5/16	4000	230	3	17.4			X	X		
	S	380	1	2	See Note#1	10061	26.5	8	7/16	4000	415	3	8.8			X	X		
	S	380	3	3	See Note#1	10061	15.3	12	7/16	4000	415	3	8.8			X	X		
	S	400	1	2	See Note#1	11148	27.9	8	7/16	4000	415	3	9.3			X	X		
	S	400	3	3	See Note#1	11148	16.1	12	7/16	4000	415	3	9.3			X	X		
	S	416	1	2	See Note#1	12058	29.0	8	7/16	4000	415	3	9.7			X	X		
	S	416	3	3	See Note#1	12058	16.7	10	7/16	4000	415	3	9.7			X	X		
S	440	1	2	See Note#1	10979	25.0	8	7/16	4000	460	3	8.3			X	X			
S	440	3	3	See Note#1	10979	14.4	12	7/16	4000	460	3	8.3			X	X			

# Rating and Approval Document

# 25 Gallon Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
KEL-25-T	S	480	1	2	See Note#1	13066	27.2	8	7/16	4000	460	3	9.1	X		X			
KEL-25	S	480	3	3	See Note#1	13066	15.7	12	7/16	4000	460	3	9.1	X		X			
KEP-25	S	575	4	2	See Note#1	12000	20.9	10	7/16	4000	575	3	7.0			X			
	S	575	3	3	See Note#1	12000	12.0	14	7/16	4000	575	3	7.0			X			
	S	600	4	2	See Note#1	13066	21.8	10	7/16	4000	575	3	7.3			X			
	S	600	3	3	See Note#1	13066	12.6	12	7/16	4000	575	3	7.3			X			
	H	200	1	2	See Note#1	13611	68.1	4	5/16	6000	230	3	22.7				X	X	
	H	200	3	3	See Note#1	13611	39.3	6	5/16	6000	230	3	22.7				X	X	
	H	208	1	2	See Note#1	14721	70.8	3	5/16	6000	230	3	23.6	X	X	X	X		
	H	208	3	3	See Note#1	14721	40.9	6	5/16	6000	230	3	23.6	X	X	X	X		
	H	240	1	2	See Note#1	19599	81.7	3	5/16	6000	230	3	27.2	X	X	X	X		
	H	240	3	3	See Note#1	19599	47.1	6	5/16	6000	230	3	27.2	X	X	X	X		
H	220	1	2	See Note#1	16469	74.9	3	5/16	6000	230	3	25.0				X	X		
H	220	3	3	See Note#1	16469	43.2	6	5/16	6000	230	3	25.0				X	X		
H	230	1	2	See Note#1	18000	78.3	3	5/16	6000	230	3	26.1				X	X		
H	230	3	3	See Note#1	18000	45.2	6	5/16	6000	230	3	26.1				X	X		

## Rating and Approval Document

## 25 Gallon Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
KEL-25-T	H	380	1	2	See Note#1	15092	39.7	6	7/16	6000	415	3	13.2	X		X	X		
KEL-25	H	380	3	3	See Note#1	15092	22.9	10	7/16	6000	415	3	13.2	X		X	X		
KEP-25	H	400	1	2	See Note#1	16722	41.8	6	7/16	6000	415	3	13.9			X	X		
	H	400	3	3	See Note#1	16722	24.1	10	7/16	6000	415	3	13.9			X	X		
	H	416	1	2	See Note#1	18087	43.5	6	7/16	6000	415	3	14.5	X		X	X		
	H	416	3	3	See Note#1	18087	25.1	8	7/16	6000	415	3	14.5	X		X	X		
	H	440	1	2	See Note#1	16469	37.4	6	7/16	6000	460	3	12.5			X	X		
	H	440	3	3	See Note#1	16469	21.6	10	7/16	6000	460	3	12.5			X	X		
	H	480	1	2	See Note#1	19599	40.8	6	7/16	6000	460	3	13.6	X		X			
	H	480	3	3	See Note#1	19599	23.6	10	7/16	6000	460	3	13.6	X		X			

**NOTES:**

- 1) Most units can be 50 or 60 Hz. Unless otherwise noted the unit will be 60 Hz.
- 2) UL and CSA approvals are for 60 Hz only.
- 3) Rating Label to be used KE95250

# Rating and Approval Document

# 30 Gallon Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
KEL-30	S	200	1	2	See Note#1	11342	56.7	4	5/16	5000	230	3	18.9			X	X		
KEL-30-T	S	200	3	3	See Note#1	11342	32.7	8	5/16	5000	230	3	18.9			X	X		
	S	208	1	2	See Note#1	12268	59.0	4	5/16	5000	230	3	19.7	X	X	X	X		
	S	208	3	3	See Note#1	12268	34.1	8	5/16	5000	230	3	19.7	X	X	X	X		
	S	240	1	2	See Note#1	16333	68.1	4	5/16	5000	230	3	22.7	X	X	X	X		
	S	240	3	3	See Note#1	16333	39.3	6	5/16	5000	230	3	22.7	X	X	X	X		
	S	220	1	2	See Note#1	13724	62.4	4	5/16	5000	230	3	20.8	X		X	X		
	S	220	3	3	See Note#1	13724	36.0	8	5/16	5000	230	3	20.8	X		X	X		
	S	230	1	2	See Note#1	15000	65.2	4	5/16	5000	230	3	21.7			X	X		
	S	230	3	3	See Note#1	15000	37.7	6	5/16	5000	230	3	21.7			X	X		
	S	380	1	2	See Note#1	12577	33.1	8	7/16	5000	415	3	11.0	X		X	X		
	S	380	3	3	See Note#1	12577	19.1	10	7/16	5000	415	3	11.0	X		X	X		
	S	400	1	2	See Note#1	13935	34.8	8	7/16	5000	415	3	11.6			X	X		
	S	400	3	3	See Note#1	13935	20.1	10	7/16	5000	415	3	11.6			X	X		
	S	416	1	2	See Note#1	15072	36.2	8	7/16	5000	415	3	12.1			X	X		
	S	416	3	3	See Note#1	15072	20.9	10	7/16	5000	415	3	12.1			X	X		

# Rating and Approval Document

# 30 Gallon Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
KEL-30	S	440	1	2	See Note#1	13724	31.2	8	7/16	5000	460	3	10.4			X	X		
KEL-30-T	S	440	3	3	See Note#1	13724	18.0	10	7/16	5000	460	3	10.4			X	X		
	S	480	1	2	See Note#1	16333	34.0	8	7/16	5000	460	3	11.3	X		X			
	S	480	3	3	See Note#1	16333	19.6	10	7/16	5000	460	3	11.3	X		X			
	S	575	1	2	See Note#1	15000	26.1	8	7/16	5000	575	3	8.7			X			
	S	575	3	3	See Note#1	15000	15.1	12	7/16	5000	575	3	8.7			X			
	S	600	1	2	See Note#1	16333	27.2	8	7/16	5000	575	3	9.1			X			
	S	600	3	3	See Note#1	16333	15.7	12	7/16	5000	575	3	9.1			X			
	H	200	3	3	See Note#1	18147	52.4	6	5/16	4000	230	6	30.2			X	X		
	H	208	3	3	See Note#1	19628	54.5	6	5/16	4000	230	6	31.5	X	X	X	X		
	H	240	3	3	See Note#1	26132	62.9	4	5/16	4000	230	6	36.3	X	X	X	X		
	H	220	3	3	See Note#1	21958	57.6	4	5/16	4000	230	6	33.3	X		X	X		
	H	230	3	3	See Note#1	24000	60.2	4	5/16	4000	230	6	34.8			X	X		
	H	380	1	2	See Note#1	20123	53.0	6	7/16	4000	415	6	17.7			X	X		
	H	380	3	3	See Note#1	20123	30.6	8	7/16	4000	415	6	17.7			X	X		
	H	400	1	2	See Note#1	22296	55.7	4	7/16	4000	415	6	18.6			X	X		
	H	400	3	3	See Note#1	22296	32.2	8	7/16	4000	415	6	18.6			X	X		

# Rating and Approval Document

# 30 Gallon Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
KEL-30	H	416	1	2	See Note#1	24116	58.0	4	7/16	4000	415	6	19.3			X	X		
KEL-30-T	H	416	3	3	See Note#1	24116	33.5	8	7/16	4000	415	6	19.3			X	X		
	H	440	1	2	See Note#1	21958	49.9	6	7/16	4000	460	6	16.6			X	X		
	H	440	3	3	See Note#1	21958	28.8	8	7/16	4000	460	6	16.6			X	X		
	H	480	1	2	See Note#1	26132	54.4	6	7/16	4000	460	6	18.1			X			
	H	480	3	3	See Note#1	26132	31.4	8	7/16	4000	460	6	18.1			X			
	H	575	1	2	See Note#1	24000	41.7	6	7/16	4000	575	6	13.9			X			
	H	575	3	3	See Note#1	24000	24.1	10	7/16	4000	575	6	13.9			X			
	H	600	1	2	See Note#1	26132	43.6	6	7/16	4000	575	6	14.5			X			
	H	600	3	3	See Note#1	26132	25.1	8	7/16	4000	575	6	14.5			X			

**NOTES:**

- 1) Most units can be 50 or 60 Hz. Unless otherwise noted the unit will be 60 Hz.
- 2) UL and CSA approvals are for 60 Hz only.
- 3) Rating Label to be used KE95250

# Rating and Approval Document

# 40 Gallon Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
KEL-40	S	200	1	2	See Note#1	13611	68.1	4	5/16	6000	230	3	22.7	X		X	X		
KEP-40	S	200	3	3	See Note#1	13611	39.3	6	5/16	6000	230	3	22.7	X		X	X		
KEL-40-T	S	208	1	2	See Note#1	14721	70.8	3	5/16	6000	230	3	23.6	X	X	X	X		
	S	208	3	3	See Note#1	14721	40.9	6	5/16	6000	230	3	23.6	X	X	X	X		
	S	240	1	2	See Note#1	19599	81.7	3	5/16	6000	230	3	27.2	X	X	X	X		
	S	240	3	3	See Note#1	19599	47.1	6	5/16	6000	230	3	27.2	X	X	X	X		
	S	220	1	2	See Note#1	16469	74.9	3	5/16	6000	230	3	25.0	X		X	X		
	S	220	3	3	See Note#1	16469	43.2	6	5/16	6000	230	3	25.0	X		X	X		
	S	230	1	2	See Note#1	18000	78.3	3	5/16	6000	230	3	26.1	X		X	X		
	S	230	3	3	See Note#1	18000	45.2	6	5/16	6000	230	3	26.1	X		X	X		
	S	380	1	2	See Note#1	15092	39.7	6	7/16	6000	415	3	13.2	X		X	X		
	S	380	3	3	See Note#1	15092	22.9	10	7/16	6000	415	3	13.2	X		X	X		
	S	400	1	2	See Note#1	16722	41.8	6	7/16	6000	415	3	13.9			X	X		
	S	400	3	3	See Note#1	16722	24.1	10	7/16	6000	415	3	13.9			X	X		
	S	416	1	2	See Note#1	18087	43.5	6	7/16	6000	415	3	14.5	X		X	X		
	S	416	3	3	See Note#1	18087	25.1	8	7/16	6000	415	3	14.5	X		X	X		

# Rating and Approval Document

# 40 Gallon Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.	
KEL-40	S	440	1	2	See Note#1	16469	37.4	6	7/16	6000	460	3	12.5			X	X			
KEP-40	S	440	3	3	See Note#1	16469	21.6	10	7/16	6000	460	3	12.5			X	X			
KEL-40-T	S	480	1	2	See Note#1	19599	40.8	6	7/16	6000	460	3	13.6	X		X				
	S	480	3	3	See Note#1	19599	23.6	10	7/16	6000	460	3	13.6	X		X				
	<del>S</del>	<del>575</del>	<del>1</del>	<del>2</del>	<del>See Note#1</del>	<del>18000</del>	<del>31.3</del>	<del>8</del>	<del>7/16</del>	<del>6000</del>	<del>575</del>	<del>3</del>	<del>10.4</del>			<del>X</del>				
	<del>S</del>	<del>575</del>	<del>3</del>	<del>3</del>	<del>See Note#1</del>	<del>18000</del>	<del>18.1</del>	<del>10</del>	<del>7/16</del>	<del>6000</del>	<del>575</del>	<del>3</del>	<del>10.4</del>			<del>X</del>				
	<del>S</del>	<del>600</del>	<del>1</del>	<del>2</del>	<del>See Note#1</del>	<del>19599</del>	<del>32.7</del>	<del>8</del>	<del>7/16</del>	<del>6000</del>	<del>575</del>	<del>3</del>	<del>10.9</del>			<del>X</del>				
	<del>S</del>	<del>600</del>	<del>3</del>	<del>3</del>	<del>See Note#1</del>	<del>19599</del>	<del>18.9</del>	<del>10</del>	<del>7/16</del>	<del>6000</del>	<del>575</del>	<del>3</del>	<del>10.9</del>			<del>X</del>				
	H	200	3	3	See Note#1	22684	65.5	4	5/16	5000	230	230	6	37.8			X	X		
	H	208	3	3	See Note#1	24535	68.1	4	5/16	5000	230	230	6	39.3	X	X	X	X		
	H	240	3	3	See Note#1	32665	78.6	3	5/16	5000	230	230	6	45.4	X	X	X	X		
	H	220	3	3	See Note#1	27448	72.0	3	5/16	5000	230	230	6	41.6	X		X	X		
	H	230	3	3	See Note#1	30000	75.3	3	5/16	5000	230	230	6	43.5	X		X	X		
	H	380	1	2	See Note#1	25153	66.2	4	7/16	5000	415	415	6	22.1	X		X	X		
	H	380	3	3	See Note#1	25153	38.2	6	7/16	5000	415	415	6	22.1	X		X	X		
	H	400	1	2	See Note#1	27871	69.7	4	7/16	5000	415	415	6	23.2			X	X		
H	400	3	3	See Note#1	27871	40.2	6	7/16	5000	415	415	6	23.2			X	X			

# Rating and Approval Document

# 40 Gallon Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
KEL-40	H	416	1	2	See Note#1	30145	72.5	3	7/16	5000	415	6	24.2	X		X	X		
KEP-40	H	416	3	3	See Note#1	30145	41.8	6	7/16	5000	415	6	24.2	X		X	X		
KEL-40-T	H	440	1	2	See Note#1	27448	62.4	4	7/16	5000	460	6	20.8			X	X		
	H	440	3	3	See Note#1	27448	36.0	8	7/16	5000	460	6	20.8			X	X		
	H	480	1	2	See Note#1	32665	68.1	4	7/16	5000	460	6	22.7	X		X			
	H	480	3	3	See Note#1	32665	39.3	6	7/16	5000	460	6	22.7	X		X			
	H	575	1	2	See Note#1	30000	52.2	6	7/16	5000	575	6	17.4			X			
	H	575	3	3	See Note#1	30000	30.1	8	7/16	5000	575	6	17.4			X			
	H	600	1	2	See Note#1	32665	54.4	6	7/16	5000	575	6	18.1			X			
	H	600	3	3	See Note#1	32665	31.4	8	7/16	5000	575	6	18.1			X			

**NOTES:**

- 1) Most units can be 50 or 60 Hz. Unless otherwise noted the unit will be 60 Hz.
- 2) UL and CSA approvals are for 60 Hz only.
- 3) Rating Label to be used KE95250

# Rating and Approval Document

# 60, 80 & 100 Gallon Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
KEL-	S	200	1	2	See Note#1	13611	68.1	4	5/16	6000	230	3	22.7			X	X		
KEL-T	S	200	3	3	See Note#1	13611	39.3	6	5/16	6000	230	3	22.7			X	X		
KEP-	S	208	1	2	See Note#1	14721	70.8	3	5/16	6000	230	3	23.6	X	X	X	X		
60/80/100	S	208	3	3	See Note#1	14721	40.9	6	5/16	6000	230	3	23.6	X	X	X	X		
KEL-40-SH	S	240	1	2	See Note#1	19599	81.7	3	5/16	6000	230	3	27.2	X	X	X	X		
KEL-60-SH	S	240	3	3	See Note#1	19599	47.1	6	5/16	6000	230	3	27.2	X	X	X	X		
KEL-80-SH	S	220	1	2	See Note#1	16469	74.9	3	5/16	6000	230	3	25.0			X	X		
KEL-40-TSH	S	220	3	3	See Note#1	16469	43.2	6	5/16	6000	230	3	25.0			X	X		
KEL-60-TSH	S	230	1	2	See Note#1	18000	78.3	3	5/16	6000	230	3	26.1			X	X		
	S	230	3	3	See Note#1	18000	45.2	6	5/16	6000	230	3	26.1			X	X		
	S	380	1	2	See Note#1	15092	39.7	6	7/16	6000	415	3	13.2	X		X	X		
	S	380	3	3	See Note#1	15092	22.9	10	7/16	6000	415	3	13.2	X		X	X		
	S	400	1	2	See Note#1	16722	41.8	6	7/16	6000	415	3	13.9			X	X		
	S	400	3	3	See Note#1	16722	24.1	10	7/16	6000	415	3	13.9			X	X		
	S	416	1	2	See Note#1	18087	43.5	6	7/16	6000	415	3	14.5	X		X	X		
	S	416	3	3	See Note#1	18087	25.1	8	7/16	6000	415	3	14.5	X		X	X		

# Rating and Approval Document

# 60, 80 & 100 Gallon Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
KEL-	S	440	1	2	See Note#1	16469	37.4	6	7/16	6000	460	3	12.5			X	X		
KEL-T	S	440	3	3	See Note#1	16469	21.6	10	7/16	6000	460	3	12.5			X	X		
KEP-	S	480	1	2	See Note#1	19599	40.8	6	7/16	6000	460	3	13.6	X		X			
60/80/100	S	480	3	3	See Note#1	19599	23.6	10	7/16	6000	460	3	13.6	X		X			
KEL-40-SH	Ⓢ	<del>575</del>	4	<del>2</del>	See Note#4	<del>48000</del>	<del>34.3</del>	8	<del>7/16</del>	<del>6000</del>	<del>575</del>	3	<del>40.4</del>			X			
KEL-60-SH	Ⓢ	<del>575</del>	3	3	See Note#4	<del>48000</del>	<del>48.4</del>	10	<del>7/16</del>	<del>6000</del>	<del>575</del>	3	<del>40.4</del>			X			
KEL-80-SH	Ⓢ	<del>600</del>	4	<del>2</del>	See Note#4	<del>49599</del>	<del>32.7</del>	8	<del>7/16</del>	<del>6000</del>	<del>575</del>	3	<del>40.9</del>			X			
KEL-40-TSH	Ⓢ	<del>600</del>	3	3	See Note#4	<del>49599</del>	<del>48.9</del>	10	<del>7/16</del>	<del>6000</del>	<del>575</del>	3	<del>40.9</del>			X			
KEL-60-TSH	H	200	3	3	See Note#1	27221	78.6	3	5/16	6000	230	6	45.4			X	X		
	H	208	3	3	See Note#1	29442	81.7	3	5/16	6000	230	6	47.2	X	X	X	X		
	H	240	3	3	See Note#1	39198	94.3	2	5/16	6000	230	6	54.4	X	X	X	X		
	H	220	3	3	See Note#1	32938	86.4	2	5/16	6000	230	6	49.9			X	X		
	H	230	3	3	See Note#1	36000	90.4	2	5/16	6000	230	6	52.2			X	X		
	H	380	1	2	See Note#1	30184	79.4	3	7/16	6000	415	6	26.5	X		X	X		
	H	380	3	3	See Note#1	30184	45.9	6	7/16	6000	415	6	26.5	X		X	X		
	H	400	1	2	See Note#1	33445	83.6	3	7/16	6000	415	6	27.9			X	X		
	H	400	3	3	See Note#1	33445	48.3	6	7/16	6000	415	6	27.9			X	X		

# Rating and Approval Document

# 60, 80 & 100 Gallon Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
KEL-	H	416	1	2	See Note#1	36174	87.0	2	7/16	6000	415	6	29.0	X		X	X		
KEL-T	H	416	3	3	See Note#1	36174	50.2	6	7/16	6000	415	6	29.0	X		X	X		
KEP-	H	440	1	2	See Note#1	32938	74.9	3	7/16	6000	460	6	25.0			X	X		
60/80/100	H	440	3	3	See Note#1	32938	43.2	6	7/16	6000	460	6	25.0			X	X		
KEL-40-SH	H	480	1	2	See Note#1	39198	81.7	3	7/16	6000	460	6	27.2	X		X			
KEL-60-SH	H	480	3	3	See Note#1	39198	47.1	6	7/16	6000	460	6	27.2	X		X			
KEL-80-SH	H	575	4	2	See Note#4	36000	62.6	4	7/16	6000	575	6	20.9			X			
KEL-40-TSH	H	575	3	3	See Note#4	36000	36.4	8	7/16	6000	575	6	20.9			X			
KEL-60-TSH																			

**NOTES:**

- 1) Most units can be 50 or 60 Hz. Unless otherwise noted the unit will be 60 Hz.
- 2) UL and CSA approvals are for 60 Hz only.
- 3) Units which are CSA certified may include optional power supply cord for units rated up to 24A max.
- 4) Rating Label to be used KE95250
- 5) Template column is for production control use only

# Rating and Approval Document

# STANDS

Model	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	UL	CSA	NSF	CE Mark
SD-450										X	
SD-650										X	
SD-760										X	
SD-1050										X	
SD-1200										X	
SD-1600										X	
SD-1800										X	
STD-28											
STD-42											
STD-55											
ST-28											
ST-42											
ST-55											

**NOTES:**

- 1) All SD stands may have the suffix K indicating NSF listed KDT-X-T Kettles mounted on stand. The K will be followed by number(s) indicating size of kettle.
- 2) Rating Label to be used KE95307

# Rating and Approval Document

Pronto

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
CA1E	S	200	1	2	See Note#1	7396	37.0	6	8000	208	1	12.3			X			
	S	200	3	3	See Note#1	7396	21.4	10	8000	208	1	12.3			X			
	S	208	1	2	See Note#1	8000	38.5	6	8000	208	1	12.8	X	X	X			
	S	208	3	3	See Note#1	8000	22.2	10	8000	208	1	12.8	X	X	X			
	S	220	1	2	See Note#1	8000	36.4	6	8000	220	1	12.1			X			
	S	220	3	3	See Note#1	8000	21.0	10	8000	220	1	12.1			X			
	S	230	1	2	See Note#1	7347	31.9	8	8000	240	1	10.6			X			
	S	230	3	3	See Note#1	7347	18.4	10	8000	240	1	10.6			X			
	S	240	1	2	See Note#1	8000	33.3	8	8000	240	1	11.1	X	X	X			
	S	240	3	3	See Note#1	8000	19.2	10	8000	240	1	11.1	X	X	X			
	S	220/380	1	2	See Note#1	8000	36.4	6	8000	220	1	12.1			X			
	S	220/380	3	4	See Note#1	8000	12.1	12	8000	220	1	12.1			X			
	S	230/400	1	2	See Note#1	7347	31.9	8	8000	240	1	10.6			X			
	S	230/400	3	4	See Note#1	7347	10.6	14	8000	240	1	10.6			X			
	S	240/415	1	2	See Note#1	8000	33.3	8	8000	240	1	11.1		X	X			
	S	240/415	3	4	See Note#1	8000	11.1	14	8000	240	1	11.1		X	X			
	S	250/440	1	2	See Note#1	8681	34.7	8	8000	240	1	11.6			X			
	S	250/440	3	4	See Note#1	8681	11.6	14	8000	240	1	11.6			X			

## Rating and Approval Document

Pronto

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
CA1E	S	380	1	2	See Note#1	8000	21.1	10	8000	380	1	7.0			X			
	S	380	3	3	See Note#1	8000	12.2	12	8000	380	1	7.0			X			
	S	400	1	2	See Note#1	7432	18.6	10	8000	415	1	6.2			X			
	S	400	3	3	See Note#1	7432	10.7	14	8000	415	1	6.2			X			
	S	415	1	2	See Note#1	8000	19.3	10	8000	415	1	6.4		X	X			
	S	415	3	3	See Note#1	8000	11.1	14	8000	415	1	6.4		X	X			
	S	440	1	2	See Note#1	6722	15.3	12	8000	480	1	5.1			X			
	S	440	3	3	See Note#1	6722	8.8	14	8000	480	1	5.1			X			
	S	480	1	2	See Note#1	8000	16.7	10	8000	480	1	5.6		X	X			
	S	480	3	3	See Note#1	8000	9.6	14	8000	480	1	5.6		X	X			
	S	575	1	2	See Note#1	7347	12.8	12	8000	600	1	4.3			X			
	S	575	3	3	See Note#1	7347	7.4	14	8000	600	1	4.3			X			
	S	600	1	2	See Note#1	8000	13.3	12	8000	600	1	4.4		X	X			
	S	600	3	3	See Note#1	8000	7.7	14	8000	600	1	4.4		X	X			

### NOTES:

- 1) Most units can be 50 or 60 Hz. Unless otherwise noted the unit will be 60 Hz.
- 2) UL and CSA approvals are for 60 Hz only.
- 3) Rating Label to be used KE95250

Rating and Approval Document					Direct Steam Kettles							
Model	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	UL	CSA	NSF	CE Mark	
KDT-1-T to KDT-12-T KDT-20-T										X	X <sup>1</sup> X	
KDL-25 to KDL-500										X	X	
KDL-30-F to KDL-150-F										X	X	
KDL-25-T to KDL-150-T	115	1	2	See Note#1	-----	4	14			X	X	
(Ratings for power tilt only)	208 to 240	1	2	See Note#1	-----	2	14			X	X	
KDM-25 to KDM-60										X	X <sup>1</sup>	
KDM-25-T to KDM-60-T	115	1	2	See Note#1	-----	2	14	X		X	X <sup>1</sup>	
(All KDM-T's are power tilt)	208 to 240	1	2	See Note#1	-----	1	14	X		X	X <sup>1</sup>	
KDP-25 to KDP-150										X	X	
KDP-25-F to KDP-125-F										X	X	
KDP-25-T to KDP-80-T	115	1	2	See Note#1	-----	4	14			X	X	
(Ratings for power tilt only)	208 to 240	1	2	See Note#1	-----	2	14			X	X	

**NOTES:**

- 1) "X1" indicates unit is self certified (Art 3 Para 3) and do not require a "CE" label.
- 2) Most units can be 50 or 60 Hz. Unless otherwise noted the unit will be 60 Hz.
- 3) UL and CSA approvals are for 60 Hz only.
- 4) Rating Label to be used KE95307 (for units without power tilt) or KE95250 ( for units with power tilt).

# Rating and Approval Document

# Table-Top Twin Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
TKET-3-T	S	200	1	2	See Note#1	7561	37.8	6	5/16	5000	230	2	18.9			X	X		
	S	208	1	2	See Note#1	8178	39.3	6	5/16	5000	230	2	19.7	X		X	X		
	S	220	1	2	See Note#1	9149	41.6	6	5/16	5000	230	2	20.8			X	X		
	S	230	1	2	See Note#1	10000	43.5	6	5/16	5000	230	2	21.7			X	X		
	S	240	1	2	See Note#1	10888	45.4	6	5/16	5000	230	2	22.7			X	X		
NOT AVAILABLE	S	380	1	2	See Note#1	8384	22.1	10	7/16	5000	415	2	11.0			X	X		
NOT AVAILABLE	S	400	1	2	See Note#1	9290	23.2	10	7/16	5000	415	2	11.6			X	X		
NOT AVAILABLE	S	415	1	2	See Note#1	10000	24.1	10	7/16	5000	415	2	12.0			X	X		
NOT AVAILABLE	S	440	1	2	See Note#1	9149	20.8	10	7/16	5000	460	2	10.4			X	X		
NOT AVAILABLE	S	480	1	2	See Note#1	10888	22.7	10	7/16	5000	460	2	11.3			X			

# Rating and Approval Document

# Table-Top Twin Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
TKET-6-T	S	200	1	2	See Note#1	11342	56.7	4	5/16	2500	230	6	9.5			X	X		
	S	200	3	3	See Note#1	11342	32.7	8	5/16	2500	230	6	9.5			X	X		
	S	208	1	2	See Note#1	12268	59.0	4	5/16	2500	230	6	9.8	X		X	X		
	S	208	3	3	See Note#1	12268	34.1	8	5/16	2500	230	6	9.8	X		X	X		
	S	240	1	2	See Note#1	16333	68.1	4	5/16	2500	230	6	11.3	X		X	X		
	S	240	3	3	See Note#1	16333	39.3	6	5/16	2500	230	6	11.3	X		X	X		
	S	220	1	2	See Note#1	13724	62.4	4	5/16	2500	230	6	10.4	X		X	X		
	S	220	3	3	See Note#1	13724	36.0	8	5/16	2500	230	6	10.4	X		X	X		
	S	230	1	2	See Note#1	15000	65.2	4	5/16	2500	230	6	10.9			X	X		
	S	230	3	3	See Note#1	15000	37.7	6	5/16	2500	230	6	10.9			X	X		
	S	380	1	2	See Note#1	12577	33.1	8	7/16	2500	415	6	5.5			X	X		
	S	380	3	3	See Note#1	12577	19.1	10	7/16	2500	415	6	5.5			X	X		
	S	400	1	2	See Note#1	13935	34.8	8	7/16	2500	415	6	5.8			X	X		
	S	400	3	3	See Note#1	13935	20.1	10	7/16	2500	415	6	5.8			X	X		
	S	415	1	2	See Note#1	15000	36.1	6	7/16	2500	415	6	6.0			X	X		
	S	415	3	3	See Note#1	15000	20.9	10	7/16	2500	415	6	6.0			X	X		
	S	440	1	2	See Note#1	13724	31.2	8	7/16	2500	460	6	5.2			X	X		
	S	440	3	3	See Note#1	13724	18.0	10	7/16	2500	460	6	5.2			X	X		
	S	480	1	2	See Note#1	16333	34.0	8	7/16	2500	460	6	5.7	X		X			
	S	480	3	3	See Note#1	16333	19.6	10	7/16	2500	460	6	5.7	X		X			

# Rating and Approval Document

# Table-Top Twin Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
TKET-6-T	S	575	1	2	See Note#1	15000	26.1	8	7/16	2500	575	6	4.3			X			
	S	575	3	3	See Note#1	15000	15.1	12	7/16	2500	575	6	4.3			X			
	S	600	1	2	See Note#1	16333	27.2	8	7/16	2500	575	6	4.5			X			
	S	600	3	3	See Note#1	16333	15.7	12	7/16	2500	575	6	4.5			X			
	H	200	3	2	See Note#1	18147	52.4	6	5/16	4000	230	6	15.1			X	X		
	H	208	3	3	See Note#1	19628	54.5	6	5/16	4000	230	6	15.7	X		X	X		
	H	220	3	2	See Note#1	21958	57.6	4	5/16	4000	230	6	16.6	X		X	X		
	H	240	3	3	See Note#1	26132	62.9	4	5/16	4000	230	6	18.1	X		X	X		
	H	230	3	3	See Note#1	24000	60.2	4	5/16	4000	230	6	17.4			X	X		
	H	380	1	2	See Note#1	20123	53.0	6	7/16	4000	415	6	8.8			X	X		
	H	380	3	3	See Note#1	20123	30.6	8	7/16	4000	415	6	8.8			X	X		
	H	400	1	2	See Note#1	22296	55.7	4	7/16	4000	415	6	9.3			X	X		
	H	400	3	3	See Note#1	22296	32.2	8	7/16	4000	415	6	9.3			X	X		
	H	415	1	2	See Note#1	24000	57.8	4	7/16	4000	415	6	9.6			X	X		
	H	415	3	3	See Note#1	24000	33.4	8	7/16	4000	415	6	9.6			X	X		
	H	440	1	2	See Note#1	21958	49.9	6	7/16	4000	460	6	8.3			X	X		
	H	440	3	3	See Note#1	21958	28.8	8	7/16	4000	460	6	8.3			X	X		
	H	480	1	2	See Note#1	26132	54.4	6	7/16	4000	460	6	9.1	X		X			
	H	480	3	3	See Note#1	26132	31.4	8	7/16	4000	460	6	9.1	X		X			

# Rating and Approval Document

# Table-Top Twin Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
TKET-12-T	S	200	1	2	See Note#1	18147	90.7	2	5/16	4000	230	6	15.1			X	X		
	S	200	3	3	See Note#1	18147	52.4	6	5/16	4000	230	6	15.1			X	X		
	S	208	1	2	See Note#1	19628	94.4	2	5/16	4000	230	6	15.7	X		X	X		
	S	208	3	3	See Note#1	19628	54.5	6	5/16	4000	230	6	15.7	X		X	X		
	S	240	1	2	See Note#1	26132	108.9	1	5/16	4000	230	6	18.1	X		X	X		
	S	240	3	3	See Note#1	26132	62.9	4	5/16	4000	230	6	18.1	X		X	X		
	S	220	1	2	See Note#1	21958	99.8	1	5/16	4000	230	6	16.6	X		X	X		
	S	220	3	3	See Note#1	21958	57.6	4	5/16	4000	230	6	16.6	X		X	X		
	S	230	1	2	See Note#1	24000	104.3	1	5/16	4000	230	6	17.4			X	X		
	S	230	3	3	See Note#1	24000	60.2	4	5/16	4000	230	6	17.4			X	X		
	S	380	1	2	See Note#1	20123	53.0	6	7/16	4000	415	6	8.8			X	X		
	S	380	3	3	See Note#1	20123	30.6	8	7/16	4000	415	6	8.8			X	X		
	S	400	1	2	See Note#1	22296	55.7	4	7/16	4000	415	6	9.3			X	X		
	S	400	3	3	See Note#1	22296	32.2	8	7/16	4000	415	6	9.3			X	X		
	S	415	1	2	See Note#1	24000	57.8	4	7/16	4000	415	6	9.6			X	X		
	S	415	3	3	See Note#1	24000	33.4	8	7/16	4000	415	6	9.6			X	X		
	S	440	1	2	See Note#1	21958	49.9	6	7/16	4000	460	6	8.3			X	X		
	S	440	3	3	See Note#1	21958	28.8	8	7/16	4000	460	6	8.3			X	X		
	S	480	1	2	See Note#1	26132	54.4	6	7/16	4000	460	6	9.1	X		X			
	S	480	3	3	See Note#1	26132	31.4	8	7/16	4000	460	6	9.1	X		X			

# Rating and Approval Document

# Table-Top Twin Electric Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
TKET-12-T	S	575	1	2	See Note#1	24000	41.7	6	7/16	4000	575	6	7.0			X			
	S	575	3	3	See Note#1	24000	24.1	10	7/16	4000	575	6	7.0			X			
	S	600	1	2	See Note#1	26132	43.6	6	7/16	4000	575	6	7.3			X			
	S	600	3	3	See Note#1	26132	25.1	8	7/16	4000	575	6	7.3			X			
	H	200	3	3	See Note#1	22684	65.5	4	5/16	5000	230	6	18.9			X	X		
	H	208	3	3	See Note#1	24535	68.1	3	5/16	5000	230	6	19.7	X		X	X		
	H	220	3	3	See Note#1	27448	72.0	3	5/16	5000	230	6	20.8	X		X	X		
	H	240	3	3	See Note#1	32665	78.6	3	5/16	5000	230	6	22.7	X		X	X		
	H	230	3	3	See Note#1	30000	75.3	3	5/16	5000	230	6	21.7			X	X		
	H	380	1	2	See Note#1	25153	66.2	4	7/16	5000	415	6	11.0			X	X		
	H	380	3	3	See Note#1	25153	38.2	6	7/16	5000	415	6	11.0			X	X		
	H	400	1	2	See Note#1	27871	69.7	3	7/16	5000	415	6	11.6			X	X		
	H	400	3	3	See Note#1	27871	40.2	6	7/16	5000	415	6	11.6			X	X		
	H	415	1	2	See Note#1	30000	72.3	3	7/16	5000	415	6	12.0	X		X	X		
	H	415	3	3	See Note#1	30000	41.7	6	7/16	5000	415	6	12.0	X		X	X		
	H	440	1	2	See Note#1	27448	62.4	4	7/16	5000	460	6	10.4			X	X		
	H	440	3	3	See Note#1	27448	36.0	8	7/16	5000	460	6	10.4			X	X		
	H	480	1	2	See Note#1	32665	68.1	4	7/16	5000	460	6	11.3	X		X			
H	480	3	3	See Note#1	32665	39.3	6	7/16	5000	460	6	11.3	X		X				

NOTE:

- 1) Most units can be 50 or 60 Hz. Unless otherwise noted the unit will be 60 Hz.
- 2) UL and CSA approvals are for 60 Hz only.
- 3) Rating Label to be used KE95250

# Rating and Approval Document

# 12 Gallon Table-Top Electric Mixer

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
MKET-12-T	S	200	1	2	See Note#1	9074	49.1	6	5/16	4000	230	3	15.1			X			
	S	200	3	3	See Note#1	9074	29.9	8	5/16	4000	230	3	15.1			X			
	S	208	1	2	See Note#1	9814	50.7	6	5/16	4000	230	3	15.7			X			
	S	208	3	3	See Note#1	9814	30.8	8	5/16	4000	230	3	15.7			X			
	S	220	1	2	See Note#1	10979	53.3	6	5/16	4000	230	3	16.6			X			
	S	220	3	3	See Note#1	10979	32.2	8	5/16	4000	230	3	16.6			X			
	S	230	1	2	See Note#1	12000	55.4	4	5/16	4000	230	3	17.4			X			
	S	230	3	3	See Note#1	12000	33.3	8	5/16	4000	230	3	17.4			X			
	S	240	1	2	See Note#1	13066	57.5	4	5/16	4000	230	3	18.1			X			
	S	240	3	3	See Note#1	13066	34.5	8	5/16	4000	230	3	18.1			X			
	S	380	1	2	See Note#1	10061	28.4	8	7/16	4000	415	3	8.8			X			
	S	380	3	3	See Note#1	10061	17.2	10	7/16	4000	415	3	8.8			X			
	S	400	1	2	See Note#1	11148	29.7	8	7/16	4000	415	3	9.3			X			
	S	400	3	3	See Note#1	11148	17.9	10	7/16	4000	415	3	9.3			X			
	S	415	1	2	See Note#1	12000	30.7	8	7/16	4000	415	3	9.6			X			
	S	415	3	3	See Note#1	12000	18.5	10	7/16	4000	415	3	9.6			X			
	S	440	1	2	See Note#1	13489	32.3	8	7/16	4000	415	3	10.2			X			
	S	440	3	3	See Note#1	13489	19.4	10	7/16	4000	415	3	10.2			X			
	S	480	1	2	See Note#1	13066	28.8	8	7/16	4000	460	3	9.1			X			
	S	480	3	3	See Note#1	13066	17.3	10	7/16	4000	460	3	9.1			X			

# Rating and Approval Document

# 12 Gallon Table-Top Electric Mixer

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
MKET-12-T	H	200	1	2	See Note#1	11342	60.4	4	5/16	5000	230	3	18.9			X			
	H	200	3	3	See Note#1	11342	36.4	8	5/16	5000	230	3	18.9			X			
	H	208	1	2	See Note#1	12268	62.5	4	5/16	5000	230	3	19.7			X			
	H	208	3	3	See Note#1	12268	37.6	6	5/16	5000	230	3	19.7			X			
	H	220	1	2	See Note#1	13724	65.7	4	5/16	5000	230	3	20.8			X			
	H	220	3	3	See Note#1	13724	39.4	6	5/16	5000	230	3	20.8			X			
	H	230	1	2	See Note#1	15000	68.4	4	5/16	5000	230	3	21.7			X			
	H	230	3	3	See Note#1	15000	40.9	6	5/16	5000	230	3	21.7			X			
	H	240	1	2	See Note#1	16333	71.1	3	5/16	5000	230	3	22.7			X			
	H	240	3	3	See Note#1	16333	42.4	6	5/16	5000	230	3	22.7			X			
	H	380	1	2	See Note#1	12577	35.0	8	7/16	5000	415	3	11.0			X			
	H	380	3	3	See Note#1	12577	21.1	10	7/16	5000	415	3	11.0			X			
	H	400	1	2	See Note#1	13935	36.7	6	7/16	5000	415	3	11.6			X			
	H	400	3	3	See Note#1	13935	22.0	10	7/16	5000	415	3	11.6			X			
	H	415	1	2	See Note#1	15000	37.9	6	7/16	5000	415	3	12.0			X			
	H	415	3	3	See Note#1	15000	22.7	10	7/16	5000	415	3	12.0			X			
	H	440	1	2	See Note#1	16862	40.0	6	7/16	5000	415	3	12.8			X			
	H	440	3	3	See Note#1	16862	23.8	10	7/16	5000	415	3	12.8			X			
	H	480	1	2	See Note#1	16333	35.6	8	7/16	5000	460	3	11.3			X			
	H	480	3	3	See Note#1	16333	21.2	10	7/16	5000	460	3	11.3			X			

## Rating and Approval Document

## 12 Gallon Table-Top Electric Mixer

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
-------	------------------	----------------	-------	-------	----	---------------	-------------	-----------	------------------	-----------------	-----------------	-----------------	---------------	----	-----	-----	---------	--------	---------

Note:

- 1) Most units can be 50 or 60 Hz. Unless otherwise noted the unit will be 60 Hz.
- 2) UL and CSA approvals are for 60 Hz only.
- 3) Supply amps. Calc. includes additional amps. for 3/4 hp. mixer motor
- 4) Rating Label to be used KE95250

# Rating and Approval Document

# 20 Gallon Table-Top Electric Mixer

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
MKET-20-T	S	200	1	2	See Note#1	11342	60.4	4	5/16	5000	230	3	18.9			X			
	S	200	3	3	See Note#1	11342	36.4	8	5/16	5000	230	3	18.9			X			
	S	208	1	2	See Note#1	12268	62.5	4	5/16	5000	230	3	19.7			X			
	S	208	3	3	See Note#1	12268	37.6	6	5/16	5000	230	3	19.7			X			
	S	220	1	2	See Note#1	13724	65.7	4	5/16	5000	230	3	20.8			X			
	S	220	3	3	See Note#1	13724	39.4	6	5/16	5000	230	3	20.8			X			
	S	230	1	2	See Note#1	15000	68.4	4	5/16	5000	230	3	21.7			X			
	S	230	3	3	See Note#1	15000	40.9	6	5/16	5000	230	3	21.7			X			
	S	240	1	2	See Note#1	16333	71.1	3	5/16	5000	230	3	22.7			X			
	S	240	3	3	See Note#1	16333	42.4	6	5/16	5000	230	3	22.7			X			
	S	380	1	2	See Note#1	12577	35.0	8	7/16	5000	415	3	11.0			X			
	S	380	3	3	See Note#1	12577	21.1	10	7/16	5000	415	3	11.0			X			
	S	400	1	2	See Note#1	13935	36.7	6	7/16	5000	415	3	11.6			X			
	S	400	3	3	See Note#1	13935	22.0	10	7/16	5000	415	3	11.6			X			
	S	415	1	2	See Note#1	15000	37.9	6	7/16	5000	415	3	12.0			X			
	S	415	3	3	See Note#1	15000	22.7	10	7/16	5000	415	3	12.0			X			
	S	440	1	2	See Note#1	13724	32.9	8	7/16	5000	460	3	10.4			X			
	S	440	3	3	See Note#1	13724	19.7	10	7/16	5000	460	3	10.4			X			
S	480	1	2	See Note#1	16333	35.6	8	7/16	5000	460	3	11.3			X				
S	480	3	3	See Note#1	16333	21.2	10	7/16	5000	460	3	11.3			X				

# Rating and Approval Document

# 20 Gallon Table-Top Electric Mixer

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.	
MKET-20-T	H	200	1	2	See Note#1	13611	71.8	3	5/16	6000	230	3	22.7			X				
	H	200	3	3	See Note#1	13611	43.0	6	5/16	6000	230	3	22.7			X				
	H	208	1	2	See Note#1	14721	74.3	3	5/16	6000	230	3	23.6			X				
	H	208	3	3	See Note#1	14721	44.4	6	5/16	6000	230	3	23.6			X				
	H	220	1	2	See Note#1	16469	78.2	3	5/16	6000	230	3	25.0			X				
	H	220	3	3	See Note#1	16469	46.6	6	5/16	6000	230	230	3	25.0			X			
	H	230	1	2	See Note#1	18000	81.5	3	5/16	6000	230	230	3	26.1			X			
	H	230	3	3	See Note#1	18000	48.4	6	5/16	6000	230	230	3	26.1			X			
	H	240	1	2	See Note#1	19599	84.7	3	5/16	6000	230	230	3	27.2			X			
	H	240	3	3	See Note#1	19599	50.2	6	5/16	6000	230	230	3	27.2			X			
	H	380	1	2	See Note#1	15092	41.7	6	7/16	6000	415	415	3	13.2			X			
	H	380	3	3	See Note#1	15092	24.9	8	7/16	6000	415	415	3	13.2			X			
	H	400	1	2	See Note#1	16722	43.7	6	7/16	6000	415	415	3	13.9			X			
	H	400	3	3	See Note#1	16722	26.0	8	7/16	6000	415	415	3	13.9			X			
	H	415	1	2	See Note#1	18000	45.2	6	7/16	6000	415	415	3	14.5			X			
	H	415	3	3	See Note#1	18000	26.8	8	7/16	6000	415	415	3	14.5			X			
	H	440	1	2	See Note#1	16469	39.1	6	7/16	6000	460	460	3	12.5			X			
	H	440	3	3	See Note#1	16469	23.3	10	7/16	6000	460	460	3	12.5			X			
H	480	1	2	See Note#1	19599	42.4	6	7/16	6000	460	460	3	13.6			X				
H	480	3	3	See Note#1	19599	25.1	8	7/16	6000	460	460	3	13.6			X				

**Note:**

- 1) Most units can be 50 or 60 Hz. Unless otherwise noted the unit will be 60 Hz.
- 2) Supply amps. Calc. includes additional amps. for 3/4 hp. mixer motor
- 3) Rating Label to be used KE95250

# Rating and Approval Document

# Electric Mixer Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
MKEL-40-T	H	200	3	3	See Note#1	22684	81.6	3	5/16	5000	230	6	37.8				X	X	
	H	208	3	3	See Note#1	24535	83.8	3	5/16	5000	230	6	39.3				X	X	
	H	220	3	3	See Note#1	27448	87.1	2	5/16	5000	230	6	41.6				X	X	
	H	230	3	3	See Note#1	30000	90.0	2	5/16	5000	230	6	43.5				X	X	
	H	240	3	3	See Note#1	32665	92.8	2	5/16	5000	230	6	45.4				X	X	
	H	380	3	3	See Note#1	25153	47.1	6	7/16	5000	415	6	22.1				X	X	
	H	400	3	3	See Note#1	27871	48.8	6	7/16	5000	415	6	23.2				X	X	
	H	415	3	3	See Note#1	30000	50.1	6	7/16	5000	415	6	24.1				X	X	
	H	440	3	3	See Note#1	27448	44.1	6	7/16	5000	460	6	20.8				X	X	
	H	480	3	3	See Note#1	32665	46.9	6	7/16	5000	460	6	22.7				X		
	H	575	3	3	See Note#1	30000	36.0	8	7/16	5000	575	6	17.4				X		
	H	600	3	3	See Note#1	32665	37.1	6	7/16	5000	575	6	18.1				X		

## Rating and Approval Document

## Electric Mixer Kettle

Model	Std/High Wattage	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
MKEL-60-T	H	200	3	3	See Note#1	27221	94.7	2	5/16	6000	230	6	45.4				X	X	
MKEL-80-T	H	208	3	3	See Note#1	29442	97.4	1	5/16	6000	230	6	47.2				X	X	
MKEL-100-T	H	220	3	3	See Note#1	32938	101.5	1	5/16	6000	230	6	49.9				X	X	
	H	230	3	3	See Note#1	36000	105.0	1	5/16	6000	230	6	52.2				X	X	
	H	240	3	3	See Note#1	39198	108.5	1	5/16	6000	230	6	54.4				X	X	
	H	380	3	3	See Note#1	30184	54.7	6	7/16	6000	415	6	26.5				X	X	
	H	400	3	3	See Note#1	33445	56.8	4	7/16	6000	415	6	27.9				X	X	
	H	415	3	3	See Note#1	36000	58.4	4	7/16	6000	415	6	28.9				X	X	
	H	440	3	3	See Note#1	32938	51.3	6	7/16	6000	460	6	25.0				X	X	
	H	480	3	3	See Note#1	39198	54.8	6	7/16	6000	460	6	27.2				X		
	H	575	3	3	See Note#1	36000	42.0	6	7/16	6000	575	6	20.9				X		
	H	600	3	3	See Note#1	39198	43.4	6	7/16	6000	575	6	21.8				X		

Note:

- 1) Most units can be 50 or 60 Hz. Unless otherwise noted the unit will be 60 Hz.
- 2) Supply Amps. Calc. Includes factor for mixer motor amps.(3hp.) plus control circuits amps.
- 3) Rating Label to be used KE95250

## Rating and Approval Document

## Twin Electric Mixer Kettle (Left & Right)

Model	Kettle Left / Right	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
TMKEL-40-T	L	200	3	3	See Note#1	22684	81.6	3	5/16	5000	230	6	37.8			X	X		
	R	200	3	3	See Note#1	22684	65.5	4	5/16	5000	230	6	37.8			X	X		
	L	208	3	3	See Note#1	24535	83.8	3	5/16	5000	230	6	39.3			X	X		
	R	208	3	3	See Note#1	24535	68.1	4	5/16	5000	230	6	39.3			X	X		
	L	220	3	3	See Note#1	27448	87.1	2	5/16	5000	230	6	41.6			X	X		
	R	220	3	3	See Note#1	27448	72.0	3	5/16	5000	230	6	41.6			X	X		
	L	230	3	3	See Note#1	30000	90.0	2	5/16	5000	230	6	43.5			X	X		
	R	230	3	3	See Note#1	30000	75.3	3	5/16	5000	230	6	43.5			X	X		
	L	240	3	3	See Note#1	32665	92.8	2	5/16	5000	230	6	45.4			X	X		
	R	240	3	3	See Note#1	32665	78.6	3	5/16	5000	230	6	45.4			X	X		
	L	380	3	3	See Note#1	25153	47.1	6	7/16	5000	415	6	22.1			X	X		
	R	380	3	3	See Note#1	25153	38.2	6	7/16	5000	415	6	22.1			X	X		

## Rating and Approval Document

## Twin Electric Mixer Kettle (Left & Right)

Model	Kettle Left / Right	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
TMKEL-40-T	L	400	3	3	See Note#1	27871	48.8	6	7/16	5000	415	6	23.2			X	X		
	R	400	3	3	See Note#1	27871	40.2	6	7/16	5000	415	6	23.2			X	X		
	L	415	3	3	See Note#1	30000	50.1	6	7/16	5000	415	6	24.1			X	X		
	R	415	3	3	See Note#1	30000	41.7	6	7/16	5000	415	6	24.1			X	X		
	L	440	3	3	See Note#1	27448	44.1	6	7/16	5000	460	6	20.8			X	X		
	R	440	3	3	See Note#1	27448	36.0	8	7/16	5000	460	6	20.8			X	X		
	L	480	3	3	See Note#1	32665	46.9	6	7/16	5000	460	6	22.7			X			
	R	480	3	3	See Note#1	32665	39.3	6	7/16	5000	460	6	22.7			X			
	L	575	3	3	See Note#1	30000	36.0	8	7/16	5000	575	6	17.4			X			
	R	575	3	3	See Note#1	30000	30.1	8	7/16	5000	575	6	17.4			X			
	L	600	3	3	See Note#1	32665	37.1	6	7/16	5000	575	6	18.1			X			
	R	600	3	3	See Note#1	32665	31.4	8	7/16	5000	575	6	18.1			X			

## Rating and Approval Document

## Twin Electric Mixer Kettle (Left & Right)

Model	Kettle Left / Right	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
TMKEL-60-T	L	200	3	3	See Note#1	27221	94.7	2	5/16	6000	230	6	45.4			X	X		
TMKEL-80-T	R	200	3	3	See Note#1	27221	78.6	3	5/16	6000	230	6	45.4			X	X		
TMKEL-100-T	L	208	3	3	See Note#1	29442	97.4	1	5/16	6000	230	6	47.2			X	X		
	R	208	3	3	See Note#1	29442	81.7	3	5/16	6000	230	6	47.2			X	X		
	L	220	3	3	See Note#1	32938	101.5	1	5/16	6000	230	6	49.9			X	X		
	R	220	3	3	See Note#1	32938	86.4	2	5/16	6000	230	6	49.9			X	X		
	L	230	3	3	See Note#1	36000	105.0	1	5/16	6000	230	6	52.2			X	X		
	R	230	3	3	See Note#1	36000	90.4	2	5/16	6000	230	6	52.2			X	X		
	L	240	3	3	See Note#1	39198	108.5	1	5/16	6000	230	6	54.4			X	X		
	R	240	3	3	See Note#1	39198	94.3	2	5/16	6000	230	6	54.4			X	X		
	L	380	3	3	See Note#1	30184	54.7	6	7/16	6000	415	6	26.5			X	X		
	R	380	3	3	See Note#1	30184	45.9	6	7/16	6000	415	6	26.5			X	X		

## Rating and Approval Document

## Twin Electric Mixer Kettle (Left & Right)

Model	Kettle Left / Right	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	Element Diameter	Element Wattage	Element Voltage	Number Elements	Amp./ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS Aus.
TMKEL-60-T	L	400	3	3	See Note#1	33445	56.8	4	7/16	6000	415	6	27.9			X	X		
TMKEL-80-T	R	400	3	3	See Note#1	33445	48.3	6	7/16	6000	415	6	27.9			X	X		
TMKEL-100-T	L	415	3	3	See Note#1	36000	58.4	4	7/16	6000	415	6	28.9			X	X		
	R	415	3	3	See Note#1	36000	50.1	6	7/16	6000	415	6	28.9			X	X		
	L	440	3	3	See Note#1	32938	51.3	6	7/16	6000	460	6	25.0			X	X		
	R	440	3	3	See Note#1	32938	43.2	6	7/16	6000	460	6	25.0			X	X		
	L	480	3	3	See Note#1	39198	54.8	6	7/16	6000	460	6	27.2			X			
	R	480	3	3	See Note#1	39198	47.1	6	7/16	6000	460	6	27.2			X			
	L	575	3	3	See Note#1	36000	42.0	6	7/16	6000	575	6	20.9			X			
	R	575	3	3	See Note#1	36000	36.1	8	7/16	6000	575	6	20.9			X			
	L	600	3	3	See Note#1	39198	43.4	6	7/16	6000	575	6	21.8			X			
	R	600	3	3	See Note#1	39198	37.7	6	7/16	6000	575	6	21.8			X			

Notes:

- 1) Most units can be 50 or 60 Hz. Unless otherwise noted the unit will be 60 Hz.
- 2) Supply Amps. for leftside kettle Calc. Includes factor for mixer motor amps.(3hp.) plus control circuits amps.
- 3) Rating labels to be used KE95280 and KE95307

# Rating and Approval Document

# GMF, LMF, AWC, CT, MFS-E, TAP

Model	Supply voltage	Phase	Wires	HZ	Total Wattage	Supply Amps	Wire Size	UL	CSA	NSF	CE Mark
<b>GMF</b>	115	1	2	See Note#1	----	1	14				
<b>LMF</b>	200 - 240	1	2	See Note#1	----	0.5	14				
<b>AWC-1</b>	115	1	2	See Note#1	----	2	14				
	200 - 240	1	2	See Note#1	----	1	14				
<b>AWC-3</b>	115	1	2	See Note#1	----	5	14				
	200 - 240	1	2	See Note#1	----	2.5	14				
<b>CT-600</b>	200 - 240	3	3	See Note#1	----	14	12				X
<b>CT-1000</b>	380 - 440	3	3	See Note#1	----	8	14				X
<b>CT-2000</b>	480	3	3	See Note#1	----	7	14				X
	575 - 600	3	3	See Note#1	----	6	14				X
<b>MFS-E</b>	115	1	2	See Note#1	----	10	14				
	220	1	2	See Note#1	----	5	14				
<b>TAP</b>	115	1	2	See Note#1	----	1	14				
	220	1	2	See Note#1	----	0.5	14				
<b>HA-DG-CC</b>	208	3	3	60	----	39	6				
	240	3	3	60	----	35	8				
<b>HA-SG-CC</b>	208	3	3	60	----	21	10				
	240	3	3	60	----	19	10				

**NOTES:**

- 1) Most units can be 50 or 60 Hz. Unless otherwise noted the unit will be 60 Hz.
- 2) Rating Label to be used KE95250

# Rating and Approval Document

# MKDL and TMKDL

Model	Supply voltage	Phase	Wires	HZ	Total wattage	Supply Amps	Wire Size	H.P.	UL	CSA	NSF	CE Mark
MKDT-12-T, MKDT-20-T	115	1	2	See Note#1	-----	8	14	0.75			X	
	200-240	1	3	See Note#1	-----	4	14	0.75			X	
MKDL-40-T to MKDL-150-T	200-208	3	3	See Note#1	-----	15	12	3			X	X
TMKDL-40-T to TMKDL-150-T	220-240	3	3	See Note#1	-----	14	12	3			X	X
	380-400	3	3	See Note#1	-----	9	14	3			X	X
	415-480	3	3	See Note#1	-----	7	14	3			X	X
	575-600	3	3	See Note#1	-----	6	14	3			X	X
MKDL-200-T to MKDL-250-T	200-208	3	3	See Note#1	-----	22	10	5			X	X
	220-240	3	3	See Note#1	-----	20	10	5			X	X
	380-400	3	3	See Note#1	-----	12	14	5			X	X
	415-480	3	3	See Note#1	-----	9	14	5			X	X
	575-600	3	3	See Note#1	-----	8	14	5			X	X

**NOTES:**

- 1) Most units can be 50 or 60 Hz. Unless otherwise noted the unit will be 60 Hz.
- 2) Rating Label used KE95250

Model	Standard Wattage	Supply Voltage	Phase	Wires	Hz	Total Wattage	Supply Amps	Wire size	Element Diameter	Element Wattage	Element Voltage	Number Element	Ample/e Pair	NRTL/C	CSA	NSF	CE Mark	TUV GS	CS Aus.
SEL-30-TR	S	208	1	2	SEE NOTE#1	14400	69.2	4	5/16	4800	208	3	23.1	X	X	X			
SEM-30-TR	S	208	3	3	SEE NOTE#1	14400	40	8	5/16	4800	208	3	23.1	X	X	X			
	S	220	1	2	SEE NOTE#1	14400	65.5	4	5/16	4800	220	3	21.8	X	X	X			
F30E-LR	S	220	3	3	SEE NOTE#1	14400	37.8	8	5/16	4800	220	3	21.8	X	X	X			
F30E-MR	S	240	1	2	SEE NOTE#1	14400	60	6	5/16	4800	240	3	20	X	X	X			
	S	240	3	3	SEE NOTE#1	14400	34.6	8	5/16	4800	240	3	20	X	X	X			
	S	347	1	2	SEE NOTE#1	14400	41.5	8	5/16	4800	347	3	13.8	X	X	X			
	S	347	3	3	SEE NOTE#1	14400	24	10	5/16	4800	347	3	13.8	X	X	X			
	S	380	1	2	SEE NOTE#1	14400	37.9	8	5/16	4800	380	3	12.6	X	X	X			
	S	380	3	3	SEE NOTE#1	14400	21.9	10	5/16	4800	380	3	12.6	X	X	X			
	S	416	1	2	SEE NOTE#1	14400	34.6	8	5/16	4800	416	3	11.5	X	X	X			
	S	416	3	3	SEE NOTE#1	14400	20	10	5/16	4800	416	3	11.5	X	X	X			
	S	480	1	2	SEE NOTE#1	14400	30	8	5/16	4800	480	3	10	X	X	X			
	S	480	3	3	SEE NOTE#1	14400	17.3	10	5/16	4800	480	3	10	X	X	X			
	S	220/380	3	4	SEE NOTE#1	14400	21.8	10	5/16	4800	220	3	21.8	X	X	X			
	S	240/415	3	4	SEE NOTE#1	14400	20	10	5/16	4800	240	3	20	X	X	X			
	S	460	3	3	SEE NOTE#1	13224	16.5	14	5/16	4800	480	3	9.6	X	X	X			
	S	600	1	2	SEE NOTE#1	14400	24	10	5/16	4800	600	3	6	X	X	X			
	S	600	3	3	SEE NOTE#1	14400	13.9	12	5/16	4800	600	3	6	X	X	X			

NOTES:

- 1) Most units can be 50 or 60 Hz. Unless otherwise noted the unit will be 60 Hz.
- 2)NRTL/C and CSA approvals are for 60Hz only.
- 3) Rating label for SEL model units is SK24967
- 4) Rating label for "F" model (Garland) units is SK2496700-1

# Rating and Approval Document

# 40 Gallon Electric Skillet

Model	Standard Wattage	Supply Voltage	Phase	Wires	Hz	Total Wattage	Supply Amps	Wire size	Element Diameter	Element Wattage	Element Voltage	Number Element	Amp/ele Pair	NRTL/C	CSA	NSF	CE Mark	TUV GS	CS Aus.
SEL-40-TR	S	208	1	2	SEE NOTE#1	18000	86.5	3	5/16	6000	208	3	28.8	X	X	X			
SEM-40-TR	S	208	3	3	SEE NOTE#1	18000	50	6	5/16	6000	208	3	28.8	X	X	X			
	S	220	1	2	SEE NOTE#1	18000	81.8	3	5/16	6000	220	3	27.3	X	X	X			
F40E-LR	S	220	3	3	SEE NOTE#1	18000	47.3	6	5/16	6000	220	3	27.3	X	X	X			
F40E-MR	S	240	1	2	SEE NOTE#1	18000	75	4	5/16	6000	240	3	25	X	X	X			
	S	240	3	3	SEE NOTE#1	18000	43.4	8	5/16	6000	240	3	25	X	X	X			
	S	347	1	2	SEE NOTE#1	18000	51.9	6	5/16	6000	347	3	17.5	X	X	X			
	S	347	3	3	SEE NOTE#1	18000	30	10	5/16	6000	347	3	17.5	X	X	X			
	S	380	1	2	SEE NOTE#1	18000	47.3	6	5/16	6000	380	3	15.8	X	X	X			
	S	380	3	3	SEE NOTE#1	18000	27.3	10	5/16	6000	380	3	15.8	X	X	X			
	S	416	1	2	SEE NOTE#1	18000	43.3	6	5/16	6000	416	3	14.3	X	X	X			
	S	416	3	3	SEE NOTE#1	18000	25	10	5/16	6000	416	3	14.3	X	X	X			
	S	480	1	2	SEE NOTE#1	18000	37.5	6	5/16	6000	480	3	12.5	X	X	X			
	S	480	3	3	SEE NOTE#1	18000	21.7	10	5/16	6000	480	3	12.5	X	X	X			
	S	220/380	3	4	SEE NOTE#1	18016	27.3	8	5/16	6000	220	3	27.3	X	X	X			
	S	240/415	3	4	SEE NOTE#1	18000	25	10	5/16	6000	240	3	25	X	X	X			
	S	460	3	3	SEE NOTE#1	16591	20.8	14	5/16	6000	480	3	12	X	X	X			
	S	600	1	2	SEE NOTE#1	18000	30	8	5/16	6000	600	3	10	X	X	X			
	S	600	3	3	SEE NOTE#1	18000	17.3	14	5/16	6000	600	3	10	X	X	X			

**NOTES:**

- 1) Most units can be 50 or 60 Hz. Unless otherwise noted the unit will be 60 Hz.
- 2) NRTL/C and CSA approvals are for 60 Hz only.
- 3) Rating label for SEL models SK2496700
- 4) Rating label for "F" model (Garland units) SK2496700-1

# Rating and Approval Document

# 10 Gallon Brazing Pan

Model	Standard Wattage	Supply Voltage	Phase	Wires	Hz	Total Wattage	Supply Amps	Wire size	Element Diameter	Element Wattage	Element Voltage	Number Element	Amp/ele Pair	UL	CSA	NSF	CE Mark	TUV GS	CS. Aus
SET-10	S	208	1	2	SEE NOTE#1	7363	35.4	6	5/16	3000	230	3	11.8	X	X	X			
	S	208	3	3	SEE NOTE#1	7363	20.4	10	5/16	3000	230	3	11.8	X	X	X			
	S	220	1	2	SEE NOTE#1	6556	29.8	8	5/16	2400	230	3	9.9	X	X	X			
	S	220	3	3	SEE NOTE#1	6556	17.2	10	5/16	2400	230	3	9.9	X	X	X			
	S	230	1	2	SEE NOTE#1	7195	31.3	8	5/16	2400	230	3	10.4	X	X	X			
	S	230	3	3	SEE NOTE#1	7195	18.1	10	5/16	2400	230	3	10.4	X	X	X			
	S	240	1	2	SEE NOTE#1	7846	32.7	8	5/16	2400	230	3	11	X	X	X			
	S	240	3	3	SEE NOTE#1	7846	18.9	10	5/16	2400	230	3	11	X	X	X			
	S	220/380	3	4	SEE NOTE#1	6556	10	14	5/16	2400	230	3	10	X	X	X			
	S	240/415	3	4	SEE NOTE#1	7846	10.9	14	5/16	2400	230	3	10.9	X	X	X			

NOTES:

- 1) Most units can be 50 or 60 Hz. Unless otherwise noted the unit will be 60 Hz.
- 2) UL and CSA approvals are for 60 Hz only.
- 3) Rating label to be used KE95250

# Rating and Approval Document

# 15 Gallon Brazing Pan

Model	Standard Wattage	Supply Voltage	Phase	Wires	Hz	Total Wattage	Supply Amps	Wire size	Element Diameter	Element Wattage	Element Voltage	Number Element	Amp/ele Pair	UL	CSA	NSF	CE MARK	TUV GS	CS.Aus
SET-15	S	208	1	2	SEE NOTE#1	7363	35.4	8	5/16	3000	230	3	11.8	X	X	X			
	S	208	3	3	SEE NOTE#1	7363	20.4	10	5/16	3000	230	3	11.8	X	X	X			
	S	220	1	2	SEE NOTE#1	6600	30	8	5/16	2400	230	3	10	X	X	X			
	S	220	3	3	SEE NOTE#1	6600	17.3	10	5/16	2400	230	3	10	X	X	X			
	S	230	1	2	SEE NOTE#1	7195	31.3	8	5/16	2400	230	3	10.4	X	X	X			
	S	230	3	3	SEE NOTE#1	7195	18.1	10	5/16	2400	230	3	10.4	X	X	X			
	S	240	1	2	SEE NOTE#1	7846	32.7	8	5/16	2400	230	3	10.9	X	X	X			
	S	240	3	3	SEE NOTE#1	7846	18.8	10	5/16	2400	230	3	10.9	X	X	X			
	S	480	1	2	SEE NOTE#1	7824	16.3	10	5/16	2400	460	3	5.4	X	X	X			
	S	480	3	3	SEE NOTE#1	7824	9.4	14	5/16	2400	460	3	5.4	X	X	X			
	S	220/380	3	4	SEE NOTE#1	6600	10	14	5/16	2400	230	3	10	X	X	X			
	S	240/415	3	4	SEE NOTE#1	7846	11	14	5/16	2400	230	3	11	X	X	X			

**NOTES:**

- 1) Most units can be 50 or 60 Hz. Unless otherwise noted the unit will be 60 Hz.
- 2) UL and CSA approvals are for 60 Hz only.
- 3) Rating label to be used KE95250

Rating and Approval Document

30 & 40 Gallon Gas Skillet

Model	Volts	Amps	Phase	Hz	BTU' per Hour	Gas Type	Water Column	BTU' per cubic foot	ANSI	Clearance Left	Clearance Right	Clearance Back	AGA	CGA	NSF	TEMPLATE
SGL-30-TR	120	1.8	1	SEE NOTE#1	91000	NAT	4.5	1000	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	0012
SGM-30-TR	120	1.8	1	SEE NOTE#1	91000	LP	10.5	2500	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	0013
POWER TILT	208	1	1	SEE NOTE#1	91000	NAT	4.5	1000	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
	208	1	1	SEE NOTE#1	91000	LP	10.5	2500	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
	220	0.9	1	SEE NOTE#1	91000	NAT	4.5	1000	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
	220	0.9	1	SEE NOTE#1	91000	LP	10.5	2500	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
	240	0.83	1	SEE NOTE#1	91000	NAT	4.5	1000	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
	240	0.83	1	SEE NOTE#1	91000	LP	10.5	2500	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
	240	0.83	1	SEE NOTE#1	91000	LP	10.5	2500	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
SGL-40-TR	120	1.8	1	SEE NOTE#1	130000	NAT	4.5	1000	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	0014
SGM-40-TR	120	1.8	1	SEE NOTE#1	130000	LP	10.5	2500	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	0015
POWER TILT	208	1	1	SEE NOTE#1	130000	NAT	4.5	1000	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
	208	1	1	SEE NOTE#1	130000	LP	10.5	2500	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
	220	0.9	1	SEE NOTE#1	130000	NAT	4.5	1000	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
	220	0.9	1	SEE NOTE#1	130000	LP	10.5	2500	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
	240	0.83	1	SEE NOTE#1	130000	NAT	4.5	1000	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
	240	0.83	1	SEE NOTE#1	130000	LP	10.5	2500	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
	240	0.83	1	SEE NOTE#1	130000	LP	10.5	2500	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
SGL-30-TR	120	0.21	1	SEE NOTE#1	91000	NAT	4.5	1000	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	0012
SGM-30-TR	120	0.21	1	SEE NOTE#1	91000	LP	10.5	2500	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	0013
HAND TILT	208	0.12	1	SEE NOTE#1	91000	NAT	4.5	1000	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
	208	0.12	1	SEE NOTE#1	91000	LP	10.5	2500	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
	220	0.11	1	SEE NOTE#1	91000	NAT	4.5	1000	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
	220	0.11	1	SEE NOTE#1	91000	LP	10.5	2500	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
	240	0.1	1	SEE NOTE#1	91000	NAT	4.5	1000	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
	240	0.1	1	SEE NOTE#1	91000	LP	10.5	2500	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
	240	0.1	1	SEE NOTE#1	91000	LP	10.5	2500	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
SGL-40-TR	120	0.21	1	SEE NOTE#1	130000	NAT	4.5	1000	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	0014
SGM-40-TR	120	0.21	1	SEE NOTE#1	130000	LP	10.5	2500	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	0015
HAND TILT	208	0.12	1	SEE NOTE#1	130000	NAT	4.5	1000	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
	208	0.12	1	SEE NOTE#1	130000	LP	10.5	2500	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	

Rating and Approval Document

30 & 40 Gallon Gas Skillet

Model	Volts	Amps	Phase	Hz	BTU' per Hour	Gas Type	Water Column	BTU' per cubic foot	ANSI	Clearance Left	Clearance Right	Clearance Back	AGA	CGA	NSF	TEMPLATE
SGL-40-TR	220	0.11	1	SEE NOTE#1	130000	NAT	4.5	1000	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
SGM-40-TR	220	0.11	1	SEE NOTE#1	130000	LP	10.5	2500	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
HAND TILT	240	0.1	1	SEE NOTE#1	130000	NAT	4.5	1000	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
	240	0.1	1	SEE NOTE#1	130000	LP	10.5	2500	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	

**NOTES:**

- 1) Most units can be 50 or 60 Hz. Unless otherwise noted the unit will be 60 Hz.
- 2) Manufactured or other types of gas must be approved and specified on an individual basis by engineering.
- 3) Rating label for USA and CANADA: KE95552
- 4) Template column is for production control use only

Rating and Approval Document

30 Gallon Electric Skillet - T1 & T4 Models

Model	Standard Wattage	Supply Voltage	Phase	Wires	Hz	Total Wattage	Supply Amps	Wire size	Element Diameter	Element Wattage	Element Voltage	Number Element	Amp/ele Pair	NRTL/C	CSA	NSF	CE Mark	TUV GS	CS Aus.
SEL-30-T4	S	208	1	2	See Note#1	12000	57.7	4	5/16	2000	208	6	19.2	X	X	X			
	S	208	3	3	See Note#1	12000	33.3	8	5/16	2000	208	6	19.2	X	X	X			
SEL-30-T1	S	220	1	2	See Note#1	10083	45.8	6	5/16	2000	240	6	15.3	X	X	X			
	S	220	3	3	See Note#1	10083	26.5	8	5/16	2000	240	6	15.3	X	X	X			
	S	240	1	2	See Note#1	12000	50.0	6	5/16	2000	240	6	16.7	X	X	X			
	S	240	3	3	See Note#1	12000	28.9	8	5/16	2000	240	6	16.7	X	X	X			
	S	380	1	2	See Note#1	10013	26.3	8	5/16	2000	416	6	8.8	X	X	X			
	S	380	3	3	See Note#1	10013	15.2	12	5/16	2000	416	6	8.8	X	X	X			
	S	416	1	2	See Note#1	12000	28.8	8	5/16	2000	416	6	9.6	X	X	X			
	S	416	3	3	See Note#1	12000	16.7	10	5/16	2000	416	6	9.6	X	X	X			
	S	480	1	2	See Note#1	12000	25.0	8	5/16	2000	480	6	8.3	X	X	X			
	S	480	3	3	See Note#1	12000	14.4	12	5/16	2000	480	6	8.3	X	X	X			
	H	208	1	2	See Note#1	16020	77.0	3	5/16	2670	208	6	25.7	X	X	X			
	H	208	3	3	See Note#1	16020	44.5	6	5/16	2670	208	6	25.7	X	X	X			
	H	220	1	2	See Note#1	13461	61.2	4	5/16	2670	240	6	20.4	X	X	X			
	H	220	3	3	See Note#1	13461	35.3	8	5/16	2670	240	6	20.4	X	X	X			
	H	240	1	2	See Note#1	16020	66.8	4	5/16	2670	240	6	22.3	X	X	X			
	H	240	3	3	See Note#1	16020	38.5	6	5/16	2670	240	6	22.3	X	X	X			
	H	380	1	2	See Note#1	13367	35.2	8	5/16	2670	416	6	11.7	X	X	X			
	H	380	3	3	See Note#1	13367	20.3	10	5/16	2670	416	6	11.7	X	X	X			
H	416	1	2	See Note#1	16020	38.5	6	5/16	2670	416	6	12.8	X	X	X				
H	416	3	3	See Note#1	16020	22.2	10	5/16	2670	416	6	12.8	X	X	X				
H	480	1	2	See Note#1	16020	33.4	8	5/16	2670	480	6	11.1	X	X	X				
H	480	3	3	See Note#1	16020	19.3	10	5/16	2670	480	6	11.1	X	X	X				

NOTES:

- 1) Most units can be 50 or 60 Hz. Unless otherwise noted the unit will be 60 Hz.
- 2)NRTL/C and CSA approvals are for 60Hz only.
- 3) Rating label to be used SK24967

## Rating and Approval Document

## 40 Gallon Electric Skillets - T1 & T4 Models

Model	Standard Wattage	Supply Voltage	Phase	Wires	Hz	Total Wattage	Supply Amps	Wire size	Element Diameter	Element Wattage	Element Voltage	Number Element	Amp/ele Pair	NRTL/C	CSA	NSF	CE Mark	TUV GS	CS Aus.
SEL-40-T4	S	208	1	2	See Note#1	18000	86.5	2	5/16	3000	208	6	28.8	X	X	X			
	S	208	3	3	See Note#1	18000	50.0	6	5/16	3000	208	6	28.8	X	X	X			
SEL40-T1	S	220	1	2	See Note#1	15125	68.8	4	5/16	3000	240	6	22.9	X	X	X			
	S	220	3	3	See Note#1	15125	39.7	6	5/16	3000	240	6	22.9	X	X	X			
	S	240	1	2	See Note#1	18000	75.0	3	5/16	3000	240	6	25.0	X	X	X			
	S	240	3	3	See Note#1	18000	43.3	6	5/16	3000	240	6	25.0	X	X	X			
	S	380	1	2	See Note#1	15019	39.5	6	5/16	3000	416	6	13.2	X	X	X			
	S	380	3	3	See Note#1	15019	22.8	10	5/16	3000	416	6	13.2	X	X	X			
	S	416	1	2	See Note#1	18000	43.3	6	5/16	3000	416	6	14.4	X	X	X			
	S	416	3	3	See Note#1	18000	25.0	8	5/16	3000	416	6	14.4	X	X	X			
	S	480	1	2	See Note#1	18000	37.5	6	5/16	3000	480	6	12.5	X	X	X			
	S	480	3	3	See Note#1	18000	21.7	10	5/16	3000	480	6	12.5	X	X	X			
	H	208	3	3	See Note#1	24000	66.6	4	5/16	4000	208	6	38.5	X	X	X			
	H	220	3	3	See Note#1	20167	52.9	6	5/16	4000	240	6	30.6	X	X	X			
	H	240	3	3	See Note#1	24000	57.7	4	5/16	4000	240	6	33.3	X	X	X			
	H	380	3	3	See Note#1	20026	30.4	8	5/16	4000	416	6	17.6	X	X	X			
	H	416	3	3	See Note#1	24000	33.3	8	5/16	4000	416	6	19.2	X	X	X			
	H	480	3	3	See Note#1	24000	28.9	8	5/16	4000	480	6	16.7	X	X	X			

### NOTES:

- 1) Most units can be 50 or 60 Hz. Unless otherwise noted the unit will be 60 Hz.
- 2)NRTL/C and CSA approvals are for 60Hz only.
- 3) Rating label to be used SK24967

# Rating and Approval Document

## 30 and 40 Gal. Gas Skillet

Model	Volts	Amps	Phase	Hz	BTU' per Hour	Gas Type	Water Column	BTU' per cubic foot	ANSI	Clearance Left	Clearance Right	Clearance Back	AGA	CGA	NSF	CE Mark
SGL-30-T4	115	1.4	1	SEE NOTE#1	125000	NAT	3.5	1025	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
SGL30-T1	115	1.4	1	SEE NOTE#1	125000	LP	10	2500	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
SGL-40-T4	115	1.4	1	SEE NOTE#1	200000	NAT	3.5	1025	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	
SGL-40-T1	115	1.4	1	SEE NOTE#1	200000	LP	10	2500	Z83.11b-2000 CGA 1.8b-2000	0	0	6	X	X	X	

**NOTE:**

- 1) Most units can be 50 or 60 Hz. Unless otherwise noted the unit will be 60 Hz.
- 2) Manufactured or other types of gas must be approved and specified on an individual basis by engineering.
- 3) Rating label for USA and CANADA: KE95552

# CE MARK Rating and Approval Document

# 30 & 40 Gallon Gas Skillets

MODEL	GAS TYPE	CE GAS TYPE	GAS PRESSURE(p)mbar	NOMINAL HEAT INPUT (Qn)		SET PRESSURE (mbar)	VOLTS	AMPS	PHASE
F30G-LR,MR F40G-LR,MR POWER TILT	NATURAL	G20	20	F30 - 24.0 Kw	F40 - 34.3 Kw	11.2	240	0.83	1
	NATURAL	G25	20	F30 - 19.6 Kw	F40 - 28.0 Kw	11.2	240	0.83	1
	NATURAL	G25	25	F30 - 19.6 Kw	F40 - 28.0 Kw	11.2	240	0.83	1
	PROPANE	G31	37	F30 - 24.5 Kw	F40 - 35.0 Kw	25	240	0.83	1
	PROPANE	G31	50	F30 - 24.5 Kw	F40 - 35.0 Kw	25	240	0.83	1
	F30G-LR,MR F40G-LR,MR MANUAL TILT	NATURAL	G20	20	F30 - 24.0 Kw	F40 - 34.3 Kw	11.2	240	0.1
MANUAL TILT	NATURAL	G25	20	F30 - 19.6 Kw	F40 - 28.0 Kw	11.2	240	0.1	1
	NATURAL	G25	25	F30 - 19.6 Kw	F40 - 28.0 Kw	11.2	240	0.1	1
	PROPANE	G31	37	F30 - 24.5 Kw	F40 - 35.0 Kw	25	240	0.1	1
	PROPANE	G31	50	F30 - 24.5 Kw	F40 - 35.0 Kw	25	240	0.1	1

**NOTE:**

1. Manufactured or other types of gas must be approved and specified on an individual basis by engineering
2. Rating label SK2471500

mbar	W.C (INS)
11.2	4.5
25	10
37	14.9
50	20.1

1 mbar = 0.4014" WC

BTU/HR	KW
66,914	19.6
81,936	24
83,643	24.5
95,592	28
117,100	34.3
119,490	35

1 kw = 3413 BTU/h

MODEL	GAS PRESSURE (KPA)		AUSTRALIAN APPROVAL No.	BURNER INPUT (MJ/h)	INJECTOR DIA. (mm)		VOLTS	AMPS	FREQ Hz	PHASE
	NAT	PROPANE			NAT	PROPANE				
F30G-LR,MR F40G-LR,MR	0.82	2.38	SC404	88.5	1.7	1.05	240	1.5	50	1
POWER TILT	0.82	2.38	SC404	126.5	1.7	1.05	240	1.5	50	1
F30G-LR,MR F40G-LR,MR	0.82	2.38	SC404	88.5	1.7	1.05	240	0.1	50	1
MANUAL TILT	0.82	2.38	SC404	126.5	1.7	1.05	240	0.1	50	1

**Notes:**

1. Manufactured or other types of gas must be approved and specified on an individual basis by engineering
2. Rating label SK02709-1

KPA	WC (INS)
0.82	3.3
2.38	9.5

1KPA=4.01"WC

MJ/h	BTU/HR
88.5	83,880
126.5	119,896

1MJ/h = 947.8 BTU/h